

AETHER 2" - Round Adjustable Trimless

R2ARAL



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Shallow housing that is designed to fit in tight plenum spaces without sacrificing lumen output.

FEATURES

- Designed to fit in tight plenum
- 2" trim aperture, 2" housing height
- Damp Location Trims: 0-30° vertical and 365° horizontal adjustment
- Wet Location Trims: 0-25° vertical and 365° horizontal adjustment
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum trim with die-cast aluminum heat sink
Dimming: 100% - 5% with 0-10V
 100% - 5% with Electronic Low Voltage (ELV)/ TRIAC
Input: 120V-277V AC
Power: 15W, power factor 0.9
Mounting: Retention clips firmly hold trim to housing
Finish: Powder Coated White, Black, Enamel Coated Haze
Ceiling thickness: 1/2" - 1"
Standards: UL & cUL Damp Listed, UL & cUL Wet Listed (Lensed options only), Title 24 JA8 Compliant

Trim (See next page for housing)	Model	Beam	Color Temp	CRI	Lumens	CBCP	Finishes	
	R2ARAL Round, 0-30° Adjustable Damp Location	S 15°	827	2700K	85	835	8045	BK Black HZ Haze WT White
			830	3000K	85	885	8535	
			835	3500K	85	905	8740	
			840	4000K	85	915	8810	
			927	2700K	90	690	6625	
			930	3000K	90	720	6935	
	R2ARAL Round, 0-25° Adjustable Lensed, Wet Location	S 16°	827	2700K	85	765	6215	LBK Lensed Black LHZ Lensed Haze LWT Lensed White
			830	3000K	85	810	6590	
			835	3500K	85	830	6750	
			840	4000K	85	840	6805	
			927	2700K	90	630	5115	
			930	3000K	90	660	5355	
R2ARAL Round, 0-25° Adjustable Lensed, Wet Location	N 26°	827	2700K	85	1270	4270	BK Black HZ Haze WT White	
		830	3000K	85	1345	4525		
		835	3500K	85	1375	4635		
		840	4000K	85	1390	4675		
		927	2700K	90	1050	3535		
		930	3000K	90	1095	3680		
R2ARAL Round, 0-25° Adjustable Lensed, Wet Location	F 40°	827	2700K	85	1260	2515	BK Black HZ Haze WT White	
		830	3000K	85	1335	2670		
		835	3500K	85	1370	2735		
		840	4000K	85	1380	2755		
		927	2700K	90	1045	2085		
		930	3000K	90	1090	2170		
R2ARAL Round, 0-25° Adjustable Lensed, Wet Location	N 28°	827	2700K	85	1175	3680	LBK Lensed Black LHZ Lensed Haze LWT Lensed White	
		830	3000K	85	1245	3905		
		835	3500K	85	1275	4000		
		840	4000K	85	1285	4030		
		927	2700K	90	970	3050		
		930	3000K	90	1015	3175		
R2ARAL Round, 0-25° Adjustable Lensed, Wet Location	F 40°	827	2700K	85	1160	2220	LBK Lensed Black LHZ Lensed Haze LWT Lensed White	
		830	3000K	85	1230	2355		
		835	3500K	85	1260	2415		
		840	4000K	85	1270	2430		
		927	2700K	90	960	1840		
		930	3000K	90	1000	1915		

R2ARAL- _____ - _____

Please see next page for housing (required)

Example: **R2ARAL-N930-WT**

wacighting.com	Headquarters, East Manufacturing Facility	South East Manufacturing Facility	Central Manufacturing Facility	West Manufacturing Facility
Phone (800) 526.2588	44 Harbor Park Drive	1600 Distribution Ct	1700 South J Elmer Freeway, Ste 100	1750 S Archibald Ave
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

AETHER 2" - Round Adjustable Trimless Housing



Housing

Model

	HR-2LED-H13A	New Construction IC-rated, Airtight
	HR-2LED-H13AC	New Construction IC-rated, Airtight Chicago Plenum

HR-2LED-H13

Example: HR-2LED-H13A

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761