

## Ion 2" Square

## Remodel Downlight

Fixture Type:
Catalog Number:
Project:
Location:

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2DSDR	<b>F</b> 35°	<b>930</b> 3000K - 90	755	1014	WT White

Example: R2DSDR-F930-WT

#### **DESCRIPTION**

Minimum profile downlight with metal conduit and driver included for easy remodel or new construction installation.

#### **FEATURES**

- Sold as remodel, but new construction frame available
- Metal Conduit with Quick Connect to allow for easy installation
- Driver included
- 5 year warranty

#### **SPECIFICATIONS**

Construction: Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver

Box

Power: 9W

Input: 120-277 VAC, 50/60Hz

**Dimming:** ELV: 100-10%, TRIAC: 100-5%

Light Source: Integrated LED
Lens: Frosted TIR lens
Rated Life: 50000 Hours

Mounting: Heavy gauge rentention clips secures fixture to ceiling

Cut Out: 3"

Finish: Electrostatically Powder Coated: White

Ceiling Thickness: 1/2" - 1 1/2"

Operating Temp:  $-4^{\circ}F$  to  $104^{\circ}F$  (-20°C to  $40^{\circ}C$ )

Standards: ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8

Compliant, IC, Airtight




#### FINISHES:



White

### **LINE DRAWING:**





# Ion 2" Square Remodel Downlight

Fixture Type:					
Catalog Number:					
Project:					
Location:					

ACCESSORIES			
	Model	Description	Finish