R2FBN1T, R2FRN1L, R2FSN1L, R2FBFT



FQ 2" Shallow - New Construction Housing and Frame-in Kit

SPECIFICATIONS			
Input	Universal 120-277V AC 50/60 Hz	Fixture Type:	
Standards:	ETL & cETL, IC-rated, Airtight (see below for list)	_	
Dimming:	Electronic Low Voltage (ELV): 100%-1% TRIAC: 100%-1% 0-10V: 100-1%	Catalog Number	:
Emergency:	EM xtures provided with integral Emergency battery back up with 24" lead wire remote test switch. Provides at least 90 minutes of 6W	Project:	
	illumination during emergency operation.		

Location:

Mounting: New construction housings included with universal mounting brackets and hanger bars

Ceiling cutout (Round and Square): Ø 3 1/2"


Ceiling thickness: 1/2" - 1"

Construction: 20 Gauge galvanized sheet

New Construction Trimmed

5 year WAC Lighting product warranty Warranty:

New Construction Trimless



HOUSINGS Model Power Rating R2FBN1T Round and Square IC New Construction Trimmed Airtight 15W Round R2FRN1L Airtight (Spackle frame included) **New Construction Trimless** 15W IC Square R2FSN1L Airtight (Spackle frame included) **New Construction** R2FBFT Round and Square 15W Non-IC Frame-in Trimmed

Example: R2FBN1T-1

waclighting.com Phone (800) 526.2588 (800) 526.2585 Headquarters, East Manufacturing Facility 44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122

Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104

West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

R2FBN1T, R2FRN1L, R2FSN1L, R2FBFT



FQ 2" Shallow - New Construction Housing and Frame-in Kit

REPLACEMENT DRIVER

Housing Model		wer	Replacement Driver Model	
R2FBN1T, R2FRN1L, R2FSN1L	1	15W	D-R2FN-1	
R2FBFT	1	15W	D-R2FF-1	

Example:

For R2FRN1L-1 housing, choose replacement driver model D-R2FN-1