

R2FRW1L

FQ 2" Shallow - Round Wall Wash Trimless



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- Light engine mounted on trim with springs for easy replacement
- 365° horizontal rotation
- Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%
TRIAC: 100%-1%
0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accomodates 1/2" - 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Title 24 JA8 Compliant.

	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R2FRW1L Round Trimless	A Asym	885	N/A	927 2700K	90	BK DB HZ WT	Black Dark Bronze Haze White
			930	N/A	930 3000K	90		
			950	N/A	935 3500K	90		

R2FRW1L - _ - _

Example: **R2FRW1L-930-WT**

Please see next page for housing units (required)

R2FRW1L

FQ 2" Shallow - Round Wall Wash Trimless



<i>HOUSING (Required)</i>		<i>Model</i>	<i>Power</i>
New Construction IC Airtight		R2FRN1L	1 15W IC
Remodel Non-IC		R2FRRL	1 15W Non-IC

R2FR ____ - ____

Example: **R2FRN1L-1**

R2FRW1L-WD

FQ 2" Shallow - Round Wall Wash Trimless (Dim-To-Warm)



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- Light engine mounted on trim with springs for easy replacement
- 365° horizontal rotation
- Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%
TRIAC: 100%-1%
0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly.
Safety cabling standard. Ceiling cutout: Ø 3 1/2"
Accommodates 1/2" - 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed,
Title 24 JA8-2019 Compliant.

	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R2FRW1L Round Trimless	A Asym	710	N/A	WD 3000K-1800K	90	BK DB HZ WT	Black Dark Bronze Haze White

R2FRW1L-__-__

Example: **R2FRW1L-WD-WT**

Please see next page for housing units (required)

R2FRW1L-WD

FQ 2" Shallow - Round Wall Wash Trimless (Dim-To-Warm)



HOUSING (Required)		Model	Power
<p>New Construction IC Airtight</p>		<p>R2FRN1L</p>	<p>1 15W IC</p>
<p>Remodel Non-IC</p>		<p>R2FRRL</p>	<p>1 15W Non-IC</p>

R2FR _____ - _____

Example: R2FRN1L-1