R2FSDT

2" FQ - Square Downlight Trim





PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- 30° shielding angle design for better visual comfort
- · Field changeable beam angle with reflectors provided
- · Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accomodates 1/2 "- 1 " ceiling thickness

Finish: Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed, Energy Star 2.0,

Title 24 JA8 Compliant.

Model	Model	В	eam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
MM T	N 25° F 40° W 55°	1880 1850 1860	4755 3115 2400	927 2700K	90				
434"	R2FSDT Square Trim	N F W	25° 40° 55°	1980 1950 1960	5005 3275 2525	930 3000K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
F 2¼" + ├── 4" ──-		N F W	25° 40° 55°	2020 1990 1995	5105 3345 2575	935 3500K		vv i vviinte	vviite

R2FSDT- -

Example: R2FSDT-927-BK (Beam N-25° reflector is pre-installed. Beams F-40° and W-55° reflectors are included.)

* Lumens and CBCP are reference values for 3000K trim with 3 housing. Use multiplier table below to determine the output for other combinations.

Multiplier		TRIM					
		927	930	935			
	3	0.95	1.00	1.02			
HOUSING	2	0.83	0.87	0.89			
1	1	0.63	0.64	0.65			

Example: **R2FSDT-930-BK** N-25° beam in **1** housing: 1980 lm (Reference Output) x 0.64 (Multiplier) = 1265 lm 5005 CBCP (Reference Output) x 0.64 (Multiplier) = 3205 CBCP

Please see next page for housing units(required)

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91761

R2FSDT

2" FQ - Square Downlight Trim



HOUSING (Required)		Model	Power		Emergency Backup
New Construction IC Airtight	10" 14%" 24"MAX	R2FBNT	1 2 3	15W IC 21W IC 25W Non-IC	EM Optional
New Construction Frame-in Non-IC	24"MAX 10" 14%" 14%" 17%" 17%" 17%" 17%" 17%" 17%" 17%" 17	R2FBFT	1 2 3	15W Non-IC 21W Non-IC 25W Non-IC	EM Optional
Remodel Non-IC	5½" — 2" — 1½" — 1½"	R2FBRT	1 2 3	15W Non-IC 21W Non-IC 25W Non-IC	N/A
Remodel IC	5½" — 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	R2FBR2T	1	15WIC	N/A

R2FB-___-

Example: R2FBNT-1 or R2FBNT-1-EM (with Emergency backup battery)

GLARE CONTROL ACCESSORIES

LENS-11-HCM	Honeycomb Louver
LENS-11P-CRL-BK	Cross Louver

LENS ACCESSORIES

LENS-11	AMB	Amber
	RED	Red
	BLU	Blue
	GRN	Green
	SPR	Spread
	BEL	Beam Elongating

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91761