### R2FSW1T

### FQ 2" Shallow - Square Wall Wash Trim





Fixture Type:	
Catalog Number:	
Destant	
Project:	
Location:	

#### PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

#### **FEATURES**

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

**Construction:** Durable die-cast aluminum construction **Input** Universal 120-277V AC 50/60 Hz

**Dimming:** Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

**Light Source:** High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accomodates 1/2 "- 1 " ceiling thickness

**Finish:** Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8 Compliant.

	Model	Beam	*Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
T 35%"	<b>R2FSW1T</b> Square Trim	A Asym	865	N/A	<b>927</b> 2700K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
+ 2½" +			910	N/A	<b>930</b> <i>3000K</i>	90		
├── 4" <del>─</del> ─┤			930	N/A	<b>935</b> 3500K	90		

R2FSW1T- -

Example: R2FSW1T-930-WT

Please see next page for housing units (required)

### R2FSW1T

# FQ 2" Shallow - Square Wall Wash Trim



HOUSING (Required)		Model	Power
New Construction IC Airtight	37/8"	R2FBN1T	<b>1</b> 15WIC
New Construction Frame-in Non-IC	24" MAX  1134"    134"    134"	R2FBFT	<b>1</b> 15W Non-IC
Remodel Non-IC	5½" —	R2FBRT	<b>1</b> 15W Non-IC

R2FB

Example: R2FBN1T-3

### R2FSW1T-WD

## FQ 2" Shallow - Square Wall Wash Trim (Dim-To-Warm)





Fixture Type:	
Catalog Number:	
Project:	
Location:	

#### **PRODUCT DESCRIPTION**

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

#### **FEATURES**

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- · 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

**Construction:** Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

**Dimming:** Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accomodates 1/2 "- 1 " ceiling thickness

**Finish:** Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8-2019 Compliant.

	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
35%" 	<b>R2FSW1T</b> Square Trim	A Asym	675	N/A	<b>WD</b> 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White

### R2FSW1T-WD-

Example: R2FSW1T-WD-WT

Please see next page for housing units (required)

### R2FSW1T-WD



# FQ 2" Shallow - Square Wall Wash Trim (Dim-To-Warm)

HOUSING (Required)		Model	Power
New Construction IC Airtight	63/6"	R2FBN1T	<b>1</b> 15WIC
New Construction Frame- in Non-IC	24" MAX	R2FBFT	<b>1</b> 15W Non-IC
Remodel Non-IC	- 5½" - 1½"  1 1½"	R2FBRT	<b>1</b> 15W Non-IC

R2FB\_\_\_-

Example: R2FBN1T-1