

# R3.5S-12W-5CCT-D90-MW 3.5" SQUARE REGRESSED DOWNLIGHT

# **RECESSED LIGHT**

## **Features**

#### Body

Diecast aluminum construction with high quality, heat resistant finish. New Construction plate is sold separately.

## **LED Specifications**

This general application light fixture is equipped with a 12 watt LED module that sustains constant efficiency by producing up to 885 Lumens; with a typical CRI of 90 and a 50,000 hour life span. Available in 2700K TO 5000K Via Switch at heat sink.

hc	rea	วิท	(	m	2	20	F
1(	102	50	- 3	ш	1	<b>ب</b> ر	г

The fixture lens provide 38° beam spread


## Location

Suitable for damp locations

SPECIFICATION					
Application	Ceiling Surface Mount				
Approved Location	Damp				
Beam Angle	38°				
CCT	2700K TO 5000K				
Certification	cETLus				
Class II	Yes				
Color	Matte White				
CRI	90				
Dimming	10%-100% (120V only)				
Input	AC120V 50/60HZ				
LM79	Yes				
LM80	Yes				
Lumens	885				
Lumens per Watt	73				
Power Factor	>0. 98				
Projected Life	70% @ 50, 000 hrs				
Warranty	3 years				
Wattage	12W				

## Photometry LIGHT DISTRIBUTION CURVE





Project						
Customer		Date				
Address						



## **Description**

The Beach Lighting 3.5" 12W LED regressed down light is suitable for most Damp locations

## **Accessories**

## R3.5-NC


New Construction Plate Sold Separately





Due to our continued efforts to improve our products, products specifications are subject to change without notice.

## **Dimensions**



Email: sales@beachlightingusa.com Ph: 1 (888) 252-8761 Fax: (954)797-7116 www.beachlightingusa.com