

WAC LIGHTING

Ocularc 3.0 5CCT

Downlight Round

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R3BRD	F 55° N 27° S 18°	CS	990	1305	BK Black
		2700K/3000K/3500K/4000K/5000K - 90	910	3150	BN Brushed Nickel
		CS	1040	8810	HZWT Haze/White
		2700K/3000K/3500K/4000K/5000K - 90			WT White
		CS			
		2700K/3000K/3500K/4000K/5000K - 90			

Example: **R3BRD-FCS-BK**

DESCRIPTION

Performance Simplified. Specializing in integrating technological advancement with forward-thinking design, Ocularc LED luminaires set the standard for residential, commercial and hospitality applications. High-performance illumination is delivered without hot spots from a single-point LED module with a clean, efficient, and versatile design from a diminutive 3-inch aperture. Its 90+ CRI ensures exceptional color rendering, while versatile dimming protocols enhance control. 5-CCT select includes warm white 2700K, 3000K, 3500K, 4000K, and 5000K.

FEATURES

- Shallow housing under 4in depth
- Ceiling thickness: 1/2" - 1 1/2"
- TIR Lens used for smooth beam
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast aluminum trim with aluminum heat sink
Power:	13W
Input:	120-277 VAC,50/60Hz
Dimming:	ELV: 100-5% , 0-10V: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED, 3 Step Mac Adam Ellipse
Rated Life:	50,000 Hours
Cut Out:	4 1/4"
Finish:	Electrostatically Powder Coated: White, Enamel Coated Haze/White, Electroplated Brushed Nickel, Black
Ceiling Thickness:	1/2" - 1 1/2"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, Airtight, IC



FINISHES:

