

Pop-In 4" Round 5CCT

Remodel Downlight

N	1odel	Beam	Color Temp & CRI	Lumens	CBCP	Finish
	R4DRDR	F 45°	9CS 2700K/3000K/3500K/4000K/500 0K - 90	870 1080	1189 1309	BK Black WT White

Example: R4DRDR-F9CS-BK

DESCRIPTION

Minimum profile downlight with driver and electrical connection box attached to fixture for easy remodel or new construction installation.

- 5-CCT Switchable between 2700K and 5000K
- Electrical box located on back of fixture to allow easy installation
- Sold as remodel, but new construction frame available
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Die-cast Aluminum with 20-gauge Cold Rolled Steel Construction:

Junction Box

12W Power:

120-277 VAC, 50/60Hz Input: ELV: 100-5%, TRIAC: 100-5% Dimming:

Integrated LED **Light Source:** Frosted TIR lens Lens: 50000 Hours Rated Life:

Heavy gauge rentention clips secures fixture to ceiling Mounting:

Cut Out:

Electrostatically Powder Coated: White, Black Finish:

1/2" - 1 1/2" Ceiling Thickness:

Operating Temp: -4°F to 104°F (-20°C to 40°C)

ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Standards:

Compliant, IC, Airtight



Fixture Type:

Project:

Location:


Catalog Number:

FINISHES:



Black White

LINE DRAWING:



R4DRDR



Pop-In 4" Round 5CCT

Remodel Downlight

Fixture Type:	
Catalog Number:	
Project:	
Location:	

ACCESSORIES							
	Model	Description	Finish				