

# WAC LIGHTING

## Pop-In 4" Square 5CCT

### New Construction Downlight

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| Model  | Beam  | Color Temp & CRI                          | Lumens      | CBCP         | Finish               |
|--------|-------|---|-------------|--------------|----------------------|
| R4DSDN | F 45° | 9CS<br>2700K/3000K/3500K/4000K/5000K - 90 | 790<br>1000 | 1207<br>1256 | BK Black<br>WT White |

Example: **R4DSDN-F9CS-BK**

#### DESCRIPTION

Minimum profile downlight with driver and electrical connection box attached to fixture for easy remodel or new construction installation.

#### FEATURES


- 5-CCT Switchable between 2700K and 5000K
- Electrical box located on back of fixture to allow easy installation
- Sold as new construction, may be configured in field for remodel
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS

|                           |   |
|---------------------------|---|
| <b>Construction:</b>      | Die-cast Aluminum with 20-gauge Cold Rolled Steel Junction Box                        |
| <b>Power:</b>             | 12W   |
| <b>Input:</b>             | 120-277 VAC, 50/60Hz  |
| <b>Dimming:</b>           | ELV: 100-5% , TRIAC: 100-5%   |
| <b>Light Source:</b>      | Integrated LED  |
| <b>Lens:</b>              | Frosted TIR lens  |
| <b>Rated Life:</b>        | 50000 Hours   |
| <b>Mounting:</b>          | New construction housings included with hanger bars                                   |
| <b>Cut Out:</b>           | 4 1/8"  |
| <b>Finish:</b>            | Electrostatically Powder Coated: White, Black   |
| <b>Ceiling Thickness:</b> | 1/2" - 1 1/2"   |
| <b>Operating Temp:</b>    | -4°F to 104°F (-20°C to 40°C)   |
| <b>Standards:</b>         | ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, IC, Airtight |



#### FINISHES:



#### LINE DRAWING:

