


## 1-LT ROUND GIMBAL

AMIGO, Recessed



### DESCRIPTION


Energy efficient hidden light sources for discreet illumination for all spaces. Designed for both commercial and residential applications, our recessed lighting provides essential directional lighting with a contemporary flare. With LED technologies constantly evolving, our new recessed collections emphasize these solutions.

### SPECIFICATIONS

MODEL	28720		
CONSTRUCTION	Forged aluminum heatsink with powder coating		
INSTALLATION TYPE	Remodel/existing ceiling		
CUT HOLE	Ø3 1/4"		
FINISH	Black/White		
MINIMUM HEIGHT CLEARANCE			
MAX CEILING THICKNESS	TRIM: 1.25" /TRIMLESS: 1.5"		
INPUT VOLTAGE	120V - 277V		
WATTAGE	15W non-IC		
DIMMING	TRIAC/ELV/0-10V		
LED PERFORMANCE	Up to 1049 Delivered Lumens ; L70: 50,000 hrs		
CCT	3000K/3500K		
BEAM ANGLE	Wide 40°		
DIFFUSERS	Clear		
ELECTRICAL APPROVAL	Compliant		
WARRANTY			
POWER SUPPLY	ERP 3 in 1 Dimmable Driver Minimum operating temperature: -30°		
ADJUSTABILITY	30°	ROTATION	NO
CRI	90+	APPROVED LOCATION	Damp

Trim

Driver Box (included):



### ORDERING INFO

CODE: \_\_\_\_\_

# OF LIGHT	SHAPE	TRIMS	LIGHT MODULE	WATTAGE	CCT	FINISHES
1-LIGHT	ROUND	TRIMMED	SLIM	15 WATT	3000K	BLACK
2-LIGHT	SQUARE	TRIMLESS	FIXED	26 WATT	3500K	WHITE
3-LIGHT			GIMBAL			

\*All features, functionality and other product specifications are subject to change without notice.

## HOUSINGS (Optional)

Description	SKU#	Suitable for	Cut Hole
New Construction Plate	30534-018	Trim	Ø3 1/4"
Smash Plate	47876-019	Trim	Ø3 1/4"
IC Box	30530-010	Trim	Ø3 1/4"
AT/IC Box	30530-026	Trim	Ø3 1/4"

\*All features, functionality and other product specifications are subject to change without notice.


## SPECIFICATIONS OPTIONS

### 1 INSTALLATION TYPE



(T) TRIMMED

### 2 COLOR FINISH



(01) BLACK



(02) WHITE



Custom

### 3 LIGHT MODULE OPTIONS



(SL)  
SLIM




(RF)  
FIXED



(RG)  
GIMBAL

### 4 CCT OPTIONS



(30) 3000K



(35) 3500K

\*All features, functionality and other product specifications are subject to change without notice.