

SURFACE MOUNT WALL WASH





DESCRIPTION

The Surface Mount Wall Wash gently spreads light through its integrated LED light bar. It comes in 2 sizes (Small and Medium) to meet any wall or hardscape lighting requirement. Dimmable with Brilliance Dimmer and most magnetic transformers. Light source UL Certified E511083.

SURFACE MOUNT WALL WASH

Use	Areas with Elevation Changes or Dark Sky Requirements Deck, Step, & Hardscape Applications
Finish	Brass, Copper, or Black Brass (Cerakote®)
Includes	Integrated Light Bar, LightingShrink Professional Crimp, and Heat Shrink Cable Connector
Integrated Lamp	Small Light Bar - 1.5W, 2700K, 110 Lumens, CRI 85, IP65, 8-15VAC, 5 year warranty SURFACE-MOUNT-WALL-WASH-SMALL-2700-COPPER SURFACE-MOUNT-WALL-WASH-SMALL-2700-BRASS SURFACE-MOUNT-WALL-WASH-SMALL-2700-BRASS-BLK
	Small Light Bar - 1.5W, 3000K, 110 Lumens, CRI 85, IP65, 8-15VAC, 5 year warranty SURFACE-MOUNT-WALL-WASH-SMALL-3000-COPPER SURFACE-MOUNT-WALL-WASH-SMALL-3000-BRASS SURFACE-MOUNT-WALL-WASH-SMALL-3000-BRASS-BLK
	Medium Light Bar - 2.5W, 2700K, 200 Lumens, CRI 85, IP65, 8-15VAC, 5 year warranty SURFACE-MOUNT-WALL-WASH-MEDIUM-2700-COPPER SURFACE-MOUNT-WALL-WASH-MEDIUM-2700-BRASS SURFACE-MOUNT-WALL-WASH-MEDIUM-2700-BRASS-BLK
	Medium Light Bar - 2.5W, 3000K, 200 Lumens, CRI 85, IP65, 8-15VAC, 5 year warranty SURFACE-MOUNT-WALL-WASH-MEDIUM-3000-COPPER SURFACE-MOUNT-WALL-WASH-MEDIUM-3000-BRASS SURFACE-MOUNT-WALL-WASH-MEDIUM-3000-BRASS-BLK



Brass



Copper



Black Brass + Cerakote®

INSTALLING THE FIXTURE

1. Separate the two-piece fixture by removing the two machine screws from the top of the body.
2. Install the wall anchors, if mounting in masonry, concrete, or sheetrock.
3. Use the provided cable connectors to connect the lead wires to the transformer main line.
4. Slide the cables into the conduit and mount the back plate onto the wall with the screws.
5. Screw the glare hood onto the fixture.