

# ELVA

6W | 480 lm | 2200K

ELVA-6W-2200K-E26-NT-120V

Elva 6W 2200K E26 Non-Tinted US LED Bulb


tala

The Elva bulb by Tala is a more compact version of the popular Gaia bulb boasting beauty and functionality. The Elva bulb is fitted with an E26 base and comes complete with a clear glass finish.




## PHYSICAL

Bulb diameter:	3 6/8in
Bulb length:	5 4/8in
Glass shape:	G30
Base:	E26
Materials:	Glass & nickel
Glass finish:	Clear
Weight:	70g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80  
— C0/C270

IES/LDT photometry files and product photography available on request



## ELECTRICAL

Power:	6W
Current:	0.05A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	80 lm/W
Lifetime:	30,000 hrs

## ILLUMINATION

CCT:	2200K
Lumens:	480 lm
Incandescent equiv.:	41W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	98
TM30 - Rf	90



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 125	Gross weight: 1.22
L 3 7/8 x W 3 7/8 x H 5 6/8in	L 20 4/8 x W 4 3/8 x H 12 2/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

## EAN

5060400151301

# ELVA

6W | 420 lm | 2200K

ELVA-6W-2200K-E26-T-120V

Elva 6W 2200K E26 Tinted US LED Bulb


The Elva bulb by Tala is a more compact version of the popular Gaia bulb boasting beauty and functionality. The Elva bulb is fitted with an E26 base and comes complete with an iron-tinted glass finish, increasing the warm, amber hues.

tala




## PHYSICAL

Bulb diameter:	3 6/8in
Bulb length:	5 4/8in
Glass shape:	G30
Base:	E26
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	70g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80  
— C0/C270

IES/LDT photometry files and product photography available on request



## ELECTRICAL

Power:	6W
Current:	0.05A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	70 lm/W
Lifetime:	30,000 hrs

## ILLUMINATION

CCT:	2200K
Lumens:	420 lm
Incandescent equiv.:	37W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 125	Gross weight: 1.22
L 3 7/8 x W 3 7/8 x H 5 6/8in	L 20 4/8 x W 4 3/8 x H 12 2/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## WARRANTY

2 years

## EAN

5060400151318

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights