

# MT-4LD4 - 4 Light (2x2)

## 4" LED Precision Multiples Energy Star®

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Retractable, adjustable spot lights

### FEATURES

- ELV and 0-10V dimming options
- Energy Star® rated
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Fully retractable from housing
- 365° horizontal rotation and 180° vertical aiming
- Accepts 1 replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

**J-Box:** Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

**Driver:** Universal (120V - 277V) or 120V input only

**Light Source:** High output LED (included with housing)





**Dimming:** 0-10V or ELV (see list of housings below)

**Mounting:** Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 9¾" x 9¾" cutout with trim, 9¾" x 9¾" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring.

**Finish:** Abrasion resistant powder coat paint in Black (BK).

**Standards:** ETL & cETL listed.


### TRIMS

		<b>MT-4LD226T</b> <i>Trim</i>	<b>WT</b> <i>White</i> <b>BK</b> <i>Black</i>
		<b>MT-4LD226TL</b> <i>Invisible Trim™</i>	<b>WT</b> <i>White</i>



Example: **MT-4LD226T-BK**

### HOUSINGS

	Power	Beam	Color Temp	CRI	Interior
	<b>MT-4LD226N</b> 0-10V dimming Non-IC, 120V-277V input 16.5W	<b>S</b> 20° <b>F</b> 40°	<b>27</b> 2700K 85 <b>927</b> 2700K 90 <b>30</b> 3000K 85 <b>930</b> 3000K 90 <b>35</b> 3500K 85 <b>40</b> 4000K 85	<b>BK</b> <i>Black</i>	
	<b>MT4LD226NE</b> ELV dimming Non-IC, 120V input 16.5W				
	<b>MT4LD221NE</b> ELV dimming IC-Rated, 120V input 11.5W				



Example: **MT-4LD226NE-S927-BK**

### REPLACEMENT LENS

Amber	<b>LENS-16-AMB</b>
Blue	<b>LENS-16-BLU</b>
Green	<b>LENS-16-GRN</b>
Red	<b>LENS-16-RED</b>
Yellow	<b>LENS-16-YEL</b>

UV Filter	<b>LENS-16-UVF</b>
Frosted	<b>LENS-16-FR</b>
Spread	<b>LENS-16-SPR</b>
Beam Elongator	<b>LENS-16-BEL</b>

WAC Lighting  
 www.waclighting.com  
 Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive • Port Washington, NY 11050  
 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center  
 1750 Archibald Avenue • Ontario, CA 91760  
 Phone (800) 526.2588 • Fax (800) 526.2585

# MT-4LD4 - 4 Light (2x2)

## 4" LED Precision Multiples Energy Star®

# WAC LIGHTING

Responsible Lighting®

LUMINAIRE PERFORMANCE	Power	Beam	Photometry	Color Temp	CRI	Lumen	CBCP
<b>MT-4LD226N</b> 0-10V dimming Non-IC, 120V-277V input	16.5W	S 20°		27 2700K 85 3680 4490 x4			
				927 2700K 90 3160 3605 x4			
				30 3000K 85 3840 4790 x4			
				930 3000K 90 3260 3910 x4			
				35 3500K 85 3900 4720 x4			
				40 4000K 85 4400 5370 x4			
<b>MT4LD226NE</b> ELV dimming Non-IC, 120V input	16.5W	S 20°		27 2700K 85 3740 4506 x4			
				927 2700K 90 3040 3545 x4			
				30 3000K 85 3888 4630 x4			
				930 3000K 90 3560 4170 x4			
				35 3500K 85 4020 4700 x4			
				40 4000K 85 3940 4700 x4			
<b>MT4LD22ww1NE</b> ELV dimming IC-Rated, 120V input	11.5W	S 20°		27 2700K 85 3060 3315 x4			
				927 2700K 90 2480 2685 x4			
				30 3000K 85 2740 3575 x4			
				930 3000K 90 2540 2795 x4			
				35 3500K 85 3200 3550 x4			
				40 4000K 85 3560 3925 x4			
<b>MT4LD22ww1NE</b> ELV dimming IC-Rated, 120V input	11.5W	F 40°		27 2700K 85 3060 1670 x4			
				927 2700K 90 2440 1270 x4			
				30 3000K 85 3060 1590 x4			
				930 3000K 90 2500 1295 x4			
				35 3500K 85 3140 1640 x4			
				40 4000K 85 3540 1820 x4			

WAC Lighting  
www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center  
1750 Archibald Avenue • Ontario, CA 91760  
Phone (800) 526.2588 • Fax (800) 526.2585