

Product UL tested and specified for use with Coral Outdoor Pendants only. Not specified for use with others.

**⚠ WARNING**  
Risk of electrical shock. Disconnect power before servicing or installing luminaire.

**⚠ WARNING**  
Risk of injury or damage. Luminaire will fail if not installed properly. Follow installation instructions.

**⚠ WARNING**  
Risk of injury. Wear safety glasses and gloves during installation and servicing.

### PACKAGE CONTENTS

Ceiling Canopy, Steel Mounting Strap, 2PC Black Cord Grip, Steel Threaded Nipple, Orange Wire Nuts, 2 Mounting Screws

**Recommended Lamping:** 1 S19 LED Dimmable 6W Lamp or equivalent, maximum load not to exceed 10W

### IMPORTANT SAFETY INSTRUCTIONS

- Read all installation instructions before installing. It is important to save these instructions.
- Only install and connect assembly with power disconnected at the circuit breaker.
- Observe and follow all label information and instructions regarding dry, damp and wet location listings, warnings of installation near combustible materials and/or insulation.
- Be sure to connect ground wire to prevent electric shock or other potential hazards.
- The product must be installed in a manner consistent with the intended use and in compliance with the national electrical codes and local codes by a person familiar with the construction and operation of the product and the hazards involved.

### PREPPING FOR INSTALLATION 1

1. Carefully unpack fixture from Carton and unfurl the black suspension and power cable.
2. Open assembly kit and ensure all parts are unpacked for installation. Reference Assembly Kit Contents list above.
3. Attach mounting strap to junction box with the 2 screws provided after power has been disconnected.

### CANOPY AND SOCKET ASSEMBLY 2

1. Gently feed power cable through the bottom half of Cord Grip and out of the Steel Nipple until there is about 10 inches of cord extending from steel nipple.
2. Slide Ceiling Canopy onto power cable until it is seated atop of Cord Grip.
3. Feed power cable through the center hole of the Mounting Strap.

### ELECTRICAL CONNECTIONS 3

1. Make electrical connections to positive and grounding wires.
2. Slide Cord Grip, Nipple and Ceiling Canopy up to junction box, then screw Nipple into center hole of Mounting Strap.

### FINAL CONNECTIONS 4

1. Slide Canopy into final position and tighten Cord Grip.
2. Screw in recommended (included) lamp type until it has a tight seal inside the lamp socket, then restore power to the fixture.

INSTRUCTION SHEET S-WN040621

Halper Lighting Solutions | 5424D Hamilton Avenue, Cleveland OH 44114  
For limited product warranty, email [info@halperlightingsolutions.com](mailto:info@halperlightingsolutions.com)

©2021 Halper Lighting Solutions. All rights reserved. Note: This document is subject to change without notice.