

R3-G19AT


3" LINE VOLTAGE GU-10 NEW CONSTRUCTION HOUSING 120V Non IC Air Tight MR-16











PRODUCT DESCRIPTION

R3-G19AT housing is designed for NON-IC rated ceilings. Accommodates up to 50W GU-10 Halogen & LED lamps.

SPECIFICATIONS

HOUSING: Low 4 1/2" profile for shallow ceilings. Pre-wired .037" steel housing adjusts up to 1 3/4" ceiling thickness. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out. Non IC rated housing must be kept 3" from insulation.

AIR FLOW RESTRICTION: Airtight models are designed to restrict air flow from room into plenums in compliance to the WSEC-Washington State Energy Code (less than 2.0 CFM-Cubic Feet per Minutes)

MOUNTING: Supplied with (2) 24" adjustable bar hangers. Bar hangers equipped with (nail-less installation) 3/4" serrated barbed studs for secure mounting in wood joists. Brackets may be flattened out to accommodate 27" flat bar hangers.

JUNCTION BOX: Pre-wired, galvanized steel J-box with (4) knock-outs. Strain clamps and ground wire. Equipped with safety standard thermal protector rated for 90°C.

LABELS: ETL/CETL listed (ETL listed number: 4005878) ETL listed for through-branch wiring (4) No. 12 AWG 90°C and damp locations.

COMPATIBLE TRIMS

| Model | Description | Finish | | |
|----------|---|--|--|--|
| R3-409 | 3" ROUND SHOWER TRIM W/ FROSTED GLASS | matte white, brushed nickel, bronze, chrome | | |
| R3-421 | 3" ROUND ALZAK TRIM W/ 35° ALZAK | matte white, matte white w/ clear, chrome w/ clear | | |
| R3-488 | 3" ROUND TRIM W/ 35° ADJUSTABLE SPOT | matte white, brushed nickel, bronze | | |
| R3-493 | 3" ROUND BAFFLE TRIM W/ 35° BAFFLE | matte white, brushed nickel w/ black | | |
| R3-508 | 3" SQUARE SHOWER TRIM W/ CLEAR GLASS | matte white, brushed nickel | | |
| R3-509 | 3" SQUARE SHOWER TRIM W/ FROSTED GLASS | matte white, brushed nickel | | |
| R3-521 | 3" SQUARE TRIM W/ 35° ALZAK | matte white, matte white w/ clear, brushed nickel w/ clear | | |
| R3-555 | 3" SQUARE APERTURE W/ SQUARE TRIM | matte white, brushed nickel | | |
| R3-559 | 3" SQUARE SHOWER TRIM W/ FROSTED GLASS | matte white, brushed nickel | | |
| R3-588 | 3" SQUARE TRIM W/ 35° ADJUSTABLE SPOT | matte white, brushed nickel | | |
| R3-590 | 3" SQUARE BAFFLE TRIM | matte white, brushed nickel | | |
| R3-593 | 3" SQUARE TRIM W/ 35° ADJUSTABLE BAFFLE | matte white | | |
| R3-DR88 | 3" DIECAST SQUARE TRIM W/ 35° ADJUSTABLE SPOT | matte white, brushed nickel | | |
| R3-DR93 | 3" DIECAST SQUARE TRIM W/ 35° BAFFLE | matte white | | |
| R3-DR488 | 3" DIECAST ROUND TRIM W/ ADJUSTABLE SPOT | matte white, brushed nickel | | |
| R3-DS88 | 3" DIECAST SQUARE TRIM W/ 35° ADJUSTABLE SPOT | matte white | | |
| R3-DS90 | 3" DIECAST SQUARE TRIM W/ 35° BAFFLE | matte white, brushed nickel | | |

| R3-DS93 | 3" DIECAST SQUARE TRIM W/ 35° BAFFLE | matte white |
|---------|--------------------------------------|-------------|