

www.beachlightingusa.com



DESCRIPTION

Beach Lighting Interior Dome Lights are designed to reduce glare and improve the light quality.

Achieves soft lighting without seeing the source.

Lights are available with LED Lighting technology and offer a stylish sleek appearance.

FEATURES

Achieve soft lighting without seeing the light source.

No glare or light distortion.

Die cast aluminum body material with good heat dissipation,


Higher reflection rate reflector with nano powder sprayed on surface Use FT4 wire with high flame retardant grade Independent drive junction box, easy to replace

Can be installed in 0.5 "to 1.25" thick ceilings safe isolated power supply Flicker free stable dimming, can be compatible with multi brand dimmers

MOUNTING

ETL listed to US and Canadian standards for damp location W/Feed through. 3 Years Limited Warranty.

MOUNTING



L6BLR-14W-3/4K-D90-MW

6" ROUND RECESSED LED DOME LIGHT

Switch-selectable color temperature

SPECIFICATION			
Applications	Recessed Ceiling Mount		
Wattage	14W		
Light Output	1080lm		
CRI	>90		
2 CCT	3000K/4000K		
Driver Input	120V AC		
Power Factor	0.98		
Dimming	TRIAC Dimmers 10%-100% (120V only)		
Location	Insulated Ceiling		
Finish	Matte White		
Certification	ETL / ENERGY STAR		
Warranty	3 Year Limited for Fixture & Driver		

R2.5-4-6NC

New Construction Plate



LISTING / WARRANTY








 ETL listed to US and Canadian standards for damp location W/Feed through. ENERGY STAR

3 Years Limited Warranty.



C0/C180: ______ C90/C270: _____

Field angle(10%Imax):C0/180Left:74.0 Right:73.9 :C90/270Left:74.1 Right:73.9 Beam Angle(50%Imax):C0/180Left:70.2 Right:67.3 :C90/270Left:70.3 Right:67.8

1.0m	309.8 , 253.1 lx	\triangle	516.39cm
2.0m	77.5 , 63.3 lx		1032.78cm
3.0m	34.4 , 28.1 lx		1549.17cm
4.0m	19.4 , 15.8 lx		2065.55cm
5.0m	12.4 , 10.1 lx		2581.94cm
6.0m	8.6 , 7.0 lx		3098.33cm
7.0m	6.3 , 5.2 lx		3614.72cm
8.0m	4.8 , 4.0 lx		4131.11cm
9.0m	3.8 , 3.1 lx		4647.50cm
10.0m	3.1 , 2.5 lx		5163.88cm

Max , Ave Beam angle of C0plane137.46

APPLICATION

