



www.beachlightingusa.com



DESCRIPTION

This ultra thin recessed LED Panel is absolutely perfect for tight spaces, soffits and insulated dropped ceilings.

Recessed 6" round LED Panel with integral driver in connection box, Fits where no other recessed fixture can.

This LED is 12 watts and replaces a 65 watt halogen save up to 80% energy for same light output.

The thin panel profile with spring clips allows for quick and easy installation. Ideal for confined spaces and suitable for damp locations.

FEATURES


Retrofit or New Construction Install Directly Under Joists, Maximum Layout Flexibility.

Comes with Junction Box & Driver, No Housing Required.

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. 2" Above Ceiling Clearance Required For Driver.

MOUNTING



L6R-15W-3/4K-DW90-MW

6" ULTRA-THIN ROUND LED RECESSED PANEL LIGHT

Switch-selectable color temperature

SPECIFICATION

Applications	Recessed Ceiling Mount
Wattage	15W
Light Output	1200lm
CRI	>90
2 CCT	3000K/4000K
Driver Input	120V AC
Power Factor	0.98
Dimming	TRIAC Dimmers 10%-100% (120V only)
Location	Insulated Ceiling & Damp Locations
Finish	Matte White
Certification	ETL / ENERGY STAR
Warranty	3 Year Limited for Fixture & Driver

R2.5-4-6NC New Construction Plate




LISTING / WARRANTY



ETL listed to US and Canadian standards for damp location W/Feed through.
ENERGY STAR
3 Years Limited Warranty.

LIGHT DISTRIBUTION CURVE



C0/C180: —
 C90/C270: —
 Field angle(10%Imax):C0/180Left:81.0 Right:79.0
 :C90/270Left:81.7 Right:78.4
 Beam Angle(50%Imax):C0/180Left:55.5 Right:52.8
 :C90/270Left:56.2 Right:52.4

1.0m	403.8 , 325.9 lx	278.62cm
2.0m	100.9 , 81.5 lx	557.24cm
3.0m	44.9 , 36.2 lx	835.86cm
4.0m	25.2 , 20.4 lx	1114.48cm
5.0m	16.2 , 13.0 lx	1393.10cm
6.0m	11.2 , 9.1 lx	1671.72cm
7.0m	8.2 , 6.7 lx	1950.33cm
8.0m	6.3 , 5.1 lx	2228.95cm
9.0m	5.0 , 4.0 lx	2507.57cm
10.0m	4.0 , 3.3 lx	2786.19cm

Max , Ave Beam angle of C0plane108.57

APPLICATION

