


# Duo-puck

These robust LED pucks, equipped with a frosted lens, deliver highly efficient punches of white light, making them well-suited for under-cabinet lighting and various other applications.

UPGRADE



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
<b>4005-CC</b>	Ø2.625"	2 W	138 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	12 V
<b>K4005-CC</b>	Ø2.625"	2 W*	138 lm*			

\*Per fixture

### Specifications

12V DC LED driver required  
 Over 50,000 hours of service life  
 12" input lead with quick connector  
 24" interconnection harness included  
 Can be recessed or surface mounted  
 Switch-selectable CCT: 2700 K/3000 K/  
 3500 K/4000 K/5000 K  
 Excellent color rendering  
 Superior LED performance and lifespan  
 Smooth 360° wide spread  
 Minimal heat emission  
 Steel/aluminum construction  
 Frosted glass lens  
 Kits available  
 Refer to website for dimmer compatibility  
 5-year warranty

### Note

Plug-in or hard-wired power supply required for installation. Sold separately.  
 Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

### Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

### Power supplies: plug-in

- ETR-LED10WPI**  
12V DC/10W class 2 LED driver
- ETR-LED24WPI**  
12V DC/24W class 2 LED driver

### Power supplies: hard-wired

- DD1260**  
LED driver and dimmer in one unit
- BT06DIM-IC**  
6W dimmable LED hardwire driver
- BT12DIM-IC**  
12W dimmable LED hardwire driver
- BT24DIM-IC**  
24W dimmable LED hardwire driver
- BT36DIM**  
36W dimmable LED hardwire driver
- BT48DIM**  
48W dimmable LED hardwire driver

### Accessories

- 4000-E24**  
24" extension cord
- 4000-E60**  
60" extension cord
- 4000HRNS-24**  
24" interconnection harness

