

Project:

Constellation Galaxy Matrix Small Arrow LED Pendant Spec Sheet

SKU: 1884.16C Learn more at: https://sonnemanlight.com/constellation-galaxy-matrix-arrow-led-pendant

Description: The dazzling luminance of double-sided lensed LED hubs are captured in a mesh-like weave. The points of light radiate illumination through the option of faceted crystal or soft white lenses. Galaxy Matrix can also be customized for your project. This statement peice is easy to assemble.

Type #:

Dimensions

Height:	71
Width:	58
Length:	58
Depth:	58
Diameter:	48
Size:	Small

Electrical Specs

Bulb(s) Included?:
Bulb 1 Type:
Bulb Quantity:
Input Voltage:
Wattage:
Initial Lumens:
Delivered Lumens:
Color Temperature:
CRI:
Power Supply Type:
Power Supply Quantity:
Power Supply Location:
Dimming Type:

Yes Integral LED 120 120-277VAC 150 14000 12000 3000K 90 Driver 2 Canopy TRIAC/ELV/ 0-10V

Installation

Installation:
Sloped Ceiling Compatible?:
Cord Length:
Minimum Hanging Height: Maximum Hanging Height:

Shade

Shade 1 Material:

Available Finishes


Available Finishes: Bright Satin Aluminum w/Clear Faceted Acrylic

General Listings

Color/Finish: Dark Sky Friendly:

Certification:

cETL Bright Satin Aluminum (.16) N



Licensed electrician

required

Adapter

20'

311

Acrylic

Available

Adjustable Cable 73.25



v



Project:

Constellation Galaxy Matrix Arrow LED Pendant Spec Sheet

SKU: 1885.16C Learn more at: https://sonnemanlight.com/constellation-galaxy-matrix-arrow-led-pendant

Description: The dazzling luminance of double-sided lensed LED hubs are captured in a mesh-like weave. The points of light radiate illumination through the option of faceted crystal or soft white lenses. Galaxy Matrix can also be customized for your project. This statement peice is easy to assemble.

Type #:

Dimensions

Height:	95.25
Width:	78
Length:	78
Depth:	78
Diameter:	48
Size:	Standard
Canopy/Backplate/Base Height:	2.25

Electrical Specs

Bulb(s) Included?:
Bulb 1 Type:
Bulb Quantity:
Input Voltage:
Wattage:
Initial Lumens:
Delivered Lumens:
Color Temperature:
CRI:
Power Supply Type:
Power Supply Quantity:
Power Supply Location:
Dimming Type:

Yes Integral LED 224 120-277VAC 280 26250 22400 3000K 90 Driver 4 Canopy TRIAC/ELV/ 0-10V

Installation

Installation


Installation:
Sloped Ceiling Compatible?:
Cord Length:
Minimum Hanging Height: Maximum Hanging Height:

Shade

Shade 1 Material:

Available Finishes

Available Finishes: Bright Satin Aluminum w/Clear Faceted Acrylic



Licensed

required

Adapter

20'

Available

Adjustable Cable 97.5 335.25

Acrylic

electrician



General Listings

Color/Finish: Dark Sky Friendly:

Certification:

cETL Bright Satin Aluminum (.16) N