

CA3000-LED

3-1/2" 3000 Series - Evolution LED

IC Air Tight Remodel Housing for PAR16 LED Lamp

SPECIFICATIONS

HOUSING DETAILS 18 gauge 0.051" (1.3 mm) thickness galvanized steel.
 Approved for use in insulated ceilings in direct contact with the insulation material (except polyurethane).
 Air Tight.
 Flexible channel wire bracket (Patent Pending) made of 20 gauge steel, bending up to 45° vertically for ease of installation in confined spaces.
 Junction box can support up to 10 – 14 gauge wires or 8 – 12 gauge wires.
 Below-ceiling accessible.

MOUNTING **Cutout diameter: Ø 3-5/8" (92 mm)**
 Can fit in ceilings up to 7/8" (22 mm) thick.
 Requires a 7" (178 mm) clearance beyond the ceiling level.
 Patented hook (PAT#CAN 2,088.648 and #USA 5.377.088) for ease of installation and a perfect fit to ceiling.
 No light leakage.

LAMP **PAR16 LED 8W MAX**
 This product was designed for PAR16 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list.

VOLTAGE 120 Volts

COMPATIBLE TRIMS	R3151	S3450	T3165	T3450D
	R3151W	S3450D	T3185	T3450W
	R3152	T3000	T3200	T3650
	R3171	T3100	T3250	T3652
	R3450D	T3125	T3250DG	T3850
	R3470	T3145	T3260	
	R3652	T3145D	T3300	
	S3145	T3145DG	T3400	
	S3151	T3145W	T3400D	
	S3400	T3152	T3450	


THERMAL PROTECTION TC 194°F (90°C)

CERTIFICATION

- cULus **E343977** for damp locations
- Certified Air Tight ASTM E283

CODIFICATION EXAMPLE

CA3000-LED



ORDERING CODE

MODEL	SERIES	SOURCE
CA	3000	-LED
CA Remodel	3000 3-1/2" Series	-LED PAR16 LED Lamp

Project _____

Notes _____

Fixture Type _____

Date _____

