# PRO SERIES SQUARE

RECESSED LED

When looking for a modern design, a square lighting fixture is often the best choice. Even better, imagine being able to use a round cutout for installation. This is now a reality with the improved concept of this square panel light.







# KEY FEATURES

ENERGY STAR certified Fully dimmable Wet locations rated



## MODEL

| 7004-SQ-3K | 4" square panel light with round back,<br>9W, 3000K, 540 Lumens                     |
|------------|---|
| 7004-SQ-4K | 4" square panel light with round back,<br>9W, 4000K, 540 Lumens, white finish only  |
| 7006-SQ-3K | 6" square panel light with round back,<br>12W, 3000K, 817 Lumens, white finish only |

## SPECIFICATIONS

- Round back for easy installation.
- 120V direct connection.
- Every fixture includes a junction box with an integrated driver.
- Can be daisy chained.
- 80 CRI.
- Superior LED performance and lifespan.
- Smooth 360° wide spread.
- Minimal heat emission.
- Frosted lens.
- Edge lit technology.
- Aluminum construction.
- Very low profile.
- IC certification (suitable for direct contact with insulation).
- Air-tight certified as per ASTM E283-04.
- ENERGY STAR certified.
- Dimmable with most low-voltage electronic dimmers.
- Suitable for wet locations.
- FT4 certified wire.

### INSTALLATION

- For recessed installation, approved for insulated ceilings.
- Ideal for general lighting applications.
- Can be installed in indoor and outdoor applications.

### FINISH

SN Satin nickel (7004-SQ-3K model only)
WH White

### ACCESSORIES


7000-EXT108 118" (300 cm) extension cord 7000-EXT230


230" (584 cm) extension cord


**7004: LEDDOWNACC-RFPG4** 4 5/16" (10.9 cm) Rough-in plate

### 7006: LEDDOWNACC-RFP6

6 5/8" (16.8 cm) Rough-in plate







### **ORDERING EXAMPLE**

7004-SQ-4K-WH Would order a white 4" square panel light with 540 Lumens at 4000K.