


PowerLED puck

Making life simple for our customers is always a priority for us. With a direct 120 V driverless connection, we have accomplished our goal with our PowerLED pucks.

UPGRADE



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
6001-CC	Ø2.875"	4 W	235 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V

Specifications

12" input and output lead with quick connector
 Can be hardwired to a junction box
 Can be interconnected
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K
 Recessed or surface mounted installation
 Surface adapter included
 Superior LED performance and lifespan
 Smooth 360° wide spread
 Minimal heat emission
 Frosted lens
 Aluminum construction
 Refer to website for dimmer compatibility
 5-year warranty

Finish

- **SN** Satin Nickel
- **WH** White

Accessories

- 6000-JB**
Junction box for 120 V series with one 12" extension cord
- 6001-PC**
72" power cord
- 6001-E24**
24" extension cord
- 6001-E60**
60" extension cord

Note

Junction box model 6000-JB or power cord model 6001-PC are required for installation. Sold separately.

 Other color °T and finishes available, but may require MOQ's and longer lead times. Please contact your DAL'S representative for more information.

