
Mini-puck

Complete flexibility is available with our mini LED pucks. Feel free to recess, surface mount or direct-wire this directional puck to attain your desired lighting effect.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
LEDRDM1	Ø2"	1 W	80 lm	90 lm	80	3000 K	12 V

Specifications

12V DC LED driver required
 Over 50,000 hours of service life
 12" input lead with quick connector
 24" interconnection harness included
 Warm white light output
 Excellent color rendering
 Superior LED performance and lifespan
 Smooth 360° wide spread
 Minimal heat emission
 Can be recessed or surface mounted
 Surface adapter included
 Frosted lens
 Aluminum construction
 Gimbal LED module
 Refer to website for dimmer compatibility
 5-year warranty
 Kits available

Finish

- **BK** Black
- **SBA** Sandblasted aluminum
- **WH** White

Power supplies: plug-in

ETR-LED10WPI
 12V DC/10W class 2 LED driver

ETR-LED24WPI
 12V DC/24W class 2 LED driver

Power supplies: hard-wired

BT06DIM-IC
 6W dimmable LED hardwire driver

BT12DIM-IC
 12W dimmable LED hardwire driver

BT24DIM-IC
 24W dimmable LED hardwire driver

BT36DIM
 36W dimmable LED hardwire driver

BT48DIM
 48W dimmable LED hardwire driver

Accessories

4000-E24
 24" extension cord

4000-E60
 60" extension cord

4000HRNS-24
 24" interconnection harness

Note

Plug-in or hard-wired power supply required for installation. Sold separately.

Other color °T and finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

