



115 West Commercial Ave. Moonachie, NJ 07075

### Dimmer Compatibility Guide

PLEASE NOTE: Compatibility is based upon testing conducted by the manufacturer in a lab controlled environment. Actual results may vary.

Product Family Name:	776775	776883	776890
Item Number:	LEDB25/27K/FL/3	LED/8640/27K/FL/M/3	LEDB25/30K/FL/3
Ordering Code:			
Item Number:			
Ordering Code:			

Lamps per Dimmer

Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes		
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	SummaTech	IP86	Best	1	E	Dimm down to 18%	
	Switch	SE83-P	Best	1	E	Dimm down to 2%		
	Vista	VP06-ILZ	Good	2	E	Dimm down to 7%		
	Taggler	TG-600	Best	1	E	Dimm down to 10%		
	Clara	CL-600	Best	1	E	Dimm down to 1%		
	Sylark	S-600	Best	1	E	Dimm down to 1%		
	Maestro	MAW-600	Best	2	E	Dimm down to 6%		
	Titan	CD703-PW	Best	1	E	Dimm down to 20%		
	Harmony	CD703-PTC	Best	1	E	Dimm down to 1%		
	Legrand	Harmony	H703-PTC	Best	1	E	Dimm down to 3%	
CFL/LED	Leviton	SummaTech	IP06	Best	1	E	Dimm down to 2%	
	Switch	SE74	Best	1	E	Dimm down to 10%		
	Decora	DE72	Best	1	E	Dimm down to 8%		
	Diora Slide	DS06-ILZ	Best	1	E	Dimm down to 10%		
	Sylark	STCL-151	Best	1	E	Dimm down to 1%		
	Clara	CLVCL-153PL	Best	1	E	Dimm down to 1%		
	Maestro	MACL-153MLH	Best	1	E	Dimm down to 7%		
	Sylark	SCL-151P	Best	1	E	Dimm down to 1%		
	Taggler	TGCL-153PH	Best	2	E	Dimm down to 1%		
	Radio RA	RA2PH-1CL-1P	Best	1	E	Dimm down to 5%		
	Harmony	DC443-PTC	Best	1	E	Dimm down to 7%		
	Harmony	DC443-PTC	Best	1	E	Dimm down to 1%		
	Adorne Paddle	ADPDS15LM2	Bad	1	E	Dimm down to 18%		
	Electronic Low Voltage	Leviton	Vista	VP06	Best	1	E	Dimm down to 13%
		SummaTech	PE84	Best	1	E	Dimm down to 10%	
Decora		DE15-P	Bad	1	E	Dimm down to 42%		
Sylark Countour		CTEV-303P	Best	1	E	Dimm down to 10%		
Clara		CLVCL-303P	Best	1	E	Dimm down to 10%		
Maestro		MAELV-600	Best	1	E	Dimm down to 10%		
Sylark		SELV-303P	Best	1	E	Dimm down to 10%		
WREN		WREN-60MM-W	Best	1	E	Dimm down to 10%		
Legrand		Scene Director	SE1V	Bad	1	E	Dimm down to 27%	
Magnetic Low Voltage		Leviton	Vista	VPM-06	Best	2	E	Dimm down to 9%
	Decora	DE15-P	Best	1	E	Dimm down to 4%		
	Maestro	MAVLV-600	Best	2	E	Dimm down to 7%		
	Legrand	Harmony	DLV703-PW	Best	1	E	Dimm down to 1%	
Harmony	DLV703-PW	Best	1	E	Dimm down to 20%			
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMK1-BLZ	Best	1	E	Dimm down to 18%	
	Leviton	Decora Smart 2-Wire Technology	D2HD	Best	1	E	Dimm down to 15%	
	Leviton	Decora Wireless smart dimmer Wi-Fi	RD-28WD	Best	1	E	Dimm down to 13%	
	Leviton	Caseta Wireless smart dimmer Wi-Fi	PD-RVCL	Best	1	E	Dimm down to 7%	
	Legrand	Adorne Touch Wi-Fi TRU Universal	ADTF703RMTLW1	Best	1	E		
	Legrand	Adorne Soft Tap Wi-Fi TRU Universal	ADTF703RMTLW1	Best	1	E		
EE	2-WAVE	2WAVE	Best	1	E	Dimm down to 1%		
Universal	Leviton	Adorne SoftTap	ADTF703TU	Good	1	E	Dimm down to 24%	
	Wing Distributer	WING-W	Good	1	E	Dimm down to 2%		
	Harmony	H703PTC	Good	1	E	Dimm down to 2%		
	Adorne Whisper	ADWR703MMTLW2	Best	1	E	Dimm down to 2%		
	Adorne Touch	ADTF703MMTLW2	Best	1	E	Dimm down to 3%		
	Cooper	Dimmer-CFL	Good	1	E	Dimm down to 1%		
Clara	CLADDP-W-K-L	Good	1	E	Dimm down to 1%			

\*Maximum Tested Lamps per Dimmer: Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer. Only equipment "yes or" lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

#### Overall Rating

<b>Not Compatible</b>	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
<b>Bad</b>	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
<b>Good</b>	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
<b>Best</b>	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dba), wide dimming range - can dim down to 20% or less of light output.
<b>High End (H-E) / Dead Travel</b>	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
<b>Low End (L-E) / Dead Travel</b>	

Contact Information:  
 Bulbrite Industries Inc.  
 115 West Commercial Avenue Moonachie, New Jersey 07075  
 PHONE: 1-800-528-5555  
 FAX: 2-01-461-7108  
 Email: Productsupport@bulbrite.com  
 ©2019 Bulbrite Industries Inc.  
 All Rights Reserved.