

MODERN FORMS

Dimming Compatibility

ID E2111023V0

Product Family:

Sku Tested: FM-41706

Related Models

Test Voltage: 120V

Control Type:

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|---|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 5.0% | |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 94.0% | Flashing at high dimming level |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | N/A | Not Recommended |
| Legrand | Radiant | RH703PTUW | 120 | 10.0% | |
| Legrand | Adorne (ELV) | ADTP703TUU4 | 120 | 6.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUU4 | 120 | 8.0% | Not Recommended |
| Cooper | AL Series | AAL06 | 120 | N/A | Flashing at all dimming levels |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 5.0% | |
| Lutron | Diva | DVELV-300P | 120 | 5.0% | |
| Lutron | Maestro | MAELV-600 | 120 | 5.0% | |
| Lutron | Skylark | SELV-300P | 120 | 5.0% | |
| Leviton | Illumatech | IPE04-1LZ | 120 | 5.0% | |
| Lutron | Maestro | RRD-6NA | 120 | 5.0% | |
| Leviton | SureSlide | 6615-POW | 120 | 8.0% | |
| Leviton | Decora | DSE06-10Z | 120 | 5.0% | |
| Lutron | Caseta | PD-5NE | 120 | 5.0% | |
| Lutron | Homeworks | HRD-5NE | 120 | N/A | Flashing at all dimming levels |
| Lutron | Homeworks | HQRD-6NA | 120 | N/A | Not Recommended/Flashing at highest dimming level |
| Leviton | Renoir II | AWSMT-EBW | 120 | 6.0% | |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 5.0% | |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MACL-153M-WH | 120 | 5.0% | |
| Lutron | Diva | DVCL-153P | 120 | 5.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 77.0% | Flicker at high dimming level |
| Lutron | Ariadni | AYCL-153PH | 120 | 5.0% | |
| Lutron | Skylark | SCL-153P-WH | 120 | 5.0% | |
| Lutron | Maestro | MA-600-WH | 120 | N/A | Dimmer not responsive |
| Leviton | SureSlide | 6674-POW | 120 | 6.0% | |
| Lutron | Caseta | PD-6WCL | 120 | 5.0% | |
| Legrand | Harmony | HCL453PW | 120 | 10.0% | Flashing at low dimming level |
| Legrand | Radiant | RHCL453PW | 120 | 9.0% | Flashing at low dimming level |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.