

# MODERN FORMS

## Dimming Compatibility

ID E2201039V0

**Product Family:**

**Sku Tested:** PD-16813

**Related Models**

**Test Voltage:** 120/277V

**Control Type:** ELV, TRIAC, MLV

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer                  | Product              | Model Number  | Test Voltage (V) | Measured Dimming Range | Comments                       |
|-------------------------------|----------------------|---------------|------------------|------------------------|--------------------------------|
|                               |                      |               |                  | Low End                |                                |
| Adaptive Phase Dimmers        |                      |               |                  |                        |                                |
| Control4                      | Adaptive             | C4-APD120     | 120              | 0.3%                   |                                |
| Legrand                       | Adorne Touch (ELV)   | ADTH700RMTUM1 | 120              | 73.0%                  | Flicker at high dimming level  |
| Legrand                       | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120              | 65.0%                  | Not Recommended                |
| Legrand                       | Radiant              | RH703PTUW     | 120              | 12.0%                  |                                |
| Legrand                       | Adorne (ELV)         | ADTP703TUW4   | 120              | 12.0%                  |                                |
| Legrand                       | Adorne (TRIAC)       | ADTP703TUW4   | 120              | 11.0%                  | Not Recommended                |
| Cooper                        | AL Series            | AAL06         | 120              | 4.0%                   | Flashing at low dimming level  |
| Control4                      | Adaptive             | C4-APD277     | 277              | 0.5%                   |                                |
| Reverse Phase Dimmers (ELV)   |                      |               |                  |                        |                                |
| Lutron                        | Nova T               | NTELV-600     | 120              | 8.0%                   |                                |
| Lutron                        | Diva                 | DVELV-300P    | 120              | 4.0%                   |                                |
| Lutron                        | Maestro              | MAELV-600     | 120              | 1.0%                   |                                |
| Lutron                        | Skylark              | SELV-300P     | 120              | 4.0%                   |                                |
| Leviton                       | Illumatech           | IPE04-1LZ     | 120              | 6.0%                   |                                |
| Lutron                        | Maestro              | RRD-6NA       | 120              | 1.0%                   |                                |
| Leviton                       | SureSlide            | 6615-POW      | 120              | 15.0%                  |                                |
| Leviton                       | Decora               | DSE06-10Z     | 120              | 3.0%                   |                                |
| Lutron                        | Caseta               | PD-5NE        | 120              | 6.0%                   |                                |
| Lutron                        | Homeworks            | HRD-5NE       | 120              | N/A                    | Flashing at all dimming levels |
| Lutron                        | Homeworks            | HQRD-6NA      | 120              | 1.0%                   |                                |
| Leviton                       | Renoir II            | AWSMT-EBW     | 120              | 0.2%                   |                                |
| Lutron                        | Grafik-Eye           | GRX-3103-A-G  | 120              | 0.8%                   |                                |
| Leviton                       | Renoir II            | AWSMT-EBW     | 277              | 1.0%                   |                                |
| Lutron                        | Grafik-Eye           | GRX-3103-A-G  | 277              | 10.0%                  |                                |
| Forward Phase Dimmers (TRIAC) |                      |               |                  |                        |                                |
| Lutron                        | Maestro              | MACL-153M-WH  | 120              | 3.0%                   |                                |
| Lutron                        | Diva                 | DVCL-153P     | 120              | 0.5%                   |                                |
| Legrand                       | Adorne Paddle        | ADPD453LW2    | 120              | 17.0%                  |                                |
| Lutron                        | Ariadni              | AYCL-153PH    | 120              | 2.0%                   |                                |
| Lutron                        | Skylark              | SCL-153P-WH   | 120              | 0.5%                   |                                |
| Lutron                        | Maestro              | MA-600-WH     | 120              | 69.0%                  | Flicker at high dimming level  |
| Leviton                       | SureSlide            | 6674-POW      | 120              | 4.0%                   |                                |
| Lutron                        | Caseta               | PD-6WCL       | 120              | 11.0%                  | Flicker below 11%              |
| Legrand                       | Harmony              | HCL453PW      | 120              | 78.0%                  | Flashing at high dimming level |
| Legrand                       | Radiant              | RHCL453PW     | 120              | 82.0%                  | Flashing at high dimming level |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.