

# MODERN FORMS

## Dimming Compatibility

ID E2109039V0

**Product Family:**

**Skus Tested:** PD-40222

**Related Models**

**Test Voltage:** 120/277V

**Control Type:**

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	1.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	45.0%	Flashing at low dimming level
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	61.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	17.0%	
Legrand	Adorne (ELV)	ADTP703TUUW4	120	15.0%	
Legrand	Adorne (TRIAC)	ADTP703TUUW4	120	17.0%	Not Recommended
Cooper	AL Series	AAL06	120	2.0%	
Control4	Adaptive	C4-APD277	277	2.0%	
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	10.0%	
Lutron	Diva	DVELV-300P	120	5.0%	
Lutron	Maestro	MAELV-600	120	1.0%	
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illumatech	IPE04-1LZ	120	7.0%	
Lutron	Maestro	RRD-6NA	120	1.0%	
Leviton	SureSlide	6615-POW	120	19.0%	
Leviton	Decora	DSE06-10Z	120	4.0%	
Lutron	Caseta	PD-5NE	120	7.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at all dimming levels
Lutron	Homeworks	HQRD-6NA	120	1.0%	
Leviton	Renoir II	AWSMT-EBW	120	0.8%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	1.0%	
Leviton	Renoir II	AWSMT-EBW	277	2.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	13.0%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MAELV-153M-WH	120	3.0%	
Lutron	Diva	DVCL-153P	120	0.4%	Turn on time >0.5s at the lowest dimming level
Legrand	Adorne Paddle	ADPD453LW2	120	17.0%	
Lutron	Ariadni	AYCL-153PH	120	2.0%	
Lutron	Skylark	SCL-153P-WH	120	14.0%	Flashing at low dimming level; Turn on time >0.5s at the lowest dimming level
Lutron	Maestro	MA-600-WH	120	95.0%	Flashing at high dimming level
Leviton	SureSlide	6674-POW	120	5.0%	
Lutron	Caseta	PD-6WCL	120	3.0%	
Legrand	Harmony	HCL453PW	120	69.0%	Flashing at high dimming level; Turn on time >0.5s at the lowest dimming level
Legrand	Radiant	RHCL453PW	120	81.0%	Flashing at high dimming level

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.