



**Dimmer Compatibility Guide**

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

<b>Product Family Name:</b>	Specialty: Wedge, G4		
<b>Item Number:</b>	770571	770572	770583
<b>Ordering Code:</b>	LED2G4/30K/12	LED3G4/30K/12	LED2WEDGE/30K/12

DIMMERS		Lutron DIVA DVELV-300P	Lutron Skylark SELV-300P	Lutron Contour CTELV-300	Lutron Vieri VTELV-600M-W	Lutron Maestro MAELV-600	Leviton Illumatech IPE04
<b>TRANSFORMERS</b>	Hatch RS12-60M/LED	✓ Dims to 5%	✓ Dims to 10%	✓ Dims to 10%	✓ Dims to 10%	✓ Dims to 10%	+
	Hatch RS12-60W	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%
	Hatch VS12-60WD	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%	+ FL 1-6, dims to 1%
	Hatch RS12-60M	+ FL 1-4, dims to 1%	+ FL 1-4, dims to 1%	+ FL 1-4, dims to 1%	+ FL 1-4, dims to 1%	+ FL 1-4, dims to 1%	+ FL 1-4, dims to 1%
	Hatch RS12-80M	+ FL 1-6, dims to 20%	+ FL 1-6, dims to 20%	+ FL 1-6, dims to 20%	+ FL 1-6, dims to 20%	+ FL 1-6, dims to 20%	+ FL 1-6, dims to 40%
	Lightech LET60LW	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%
	Lightech LET75	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%
	WAC EN-1260-R2	✓ Dims to 5%	✓ Dims to 5%	✓ Dims to 5%	✓ Dims to 5%	✓ Dims to 5%	+
	WAC EN-12100-R-AR	✓ Dims to 5%	✓ Dims to 5%	✓ Dims to 5%	✓ Dims to 5%	✓ Dims to 5%	+
	Solutions NET-1075	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%
	LIF LF050C	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%	+ FL 1-6, dims to 50%

Overall Rating	
✓	Dims Down ≤ 20% (no flickering, no audible noise, wide dimming range)
+	Min 2 lamps: Dims Down ≤ 20% (minimal adjustment may be required, dead travel exists, minor audible noise)
+-	Min 3 lamps: Dims Down ≤ 20% (flickering observed, steppy dimming appears, voltage reverse, audible noise may be present)
NC	Not Compatible (major flickering observed, audible noise, no dimming range, does not turn off)

Contact Information:  
Bulbrite Industries Inc.  
145 West Commercial Avenue  
Moonachie, New Jersey 07074  
PHONE: 1-800-528-5555  
FAX: 1-800-441-7708  
Email: ProductSupport@bulbrite.com  
©2017 Bulbrite Industries Inc.  
All Rights Reserved.