

MODERN FORMS

Dimming Compatibility

ID E2209048V0

Product Family:

Sku Tested: PD-76350

Related Models

Test Voltage: 120-277V

Control Type: ELV,TRIAC,MLV,0-10V

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|--|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 0.1% | |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 5.0% | |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | 3.0% | Not Recommended |
| Legrand | Radiant | RH703PTUW | 120 | 5.0% | |
| Legrand | Adorne (ELV) | ADTP703TUW4 | 120 | 7.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUW4 | 120 | 5.0% | Not Recommended |
| Cooper | AL Series | AAL06 | 120 | 4.0% | |
| Control4 | Adaptive | C4-APD277 | 277 | 3.0% | |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 5.0% | |
| Lutron | Diva | DVELV-300P | 120 | 5.0% | |
| Lutron | Maestro | MAELV-600 | 120 | 2.0% | |
| Lutron | Skylark | SELV-300P | 120 | 5.0% | Turn on time >0.5s at the lowest dimming level |
| Leviton | Illumatech | IPE04-1LZ | 120 | 5.0% | |
| Lutron | Maestro | RRD-6NA | 120 | 2.0% | |
| Leviton | SureSlide | 6615-P0W | 120 | 11.0% | |
| Leviton | Decora | DSE06-10Z | 120 | 5.0% | |
| Lutron | Caseta | PD-5NE | 120 | 5.0% | |
| Lutron | Homeworks | HRD-5NE | 120 | 5.0% | |
| Lutron | Homeworks | HQRD-6NA | 120 | 2.0% | |
| Leviton | Renoir II | AWSMT-EBW | 120 | 1.0% | |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 1.0% | |
| Leviton | Renoir II | AWSMT-EBW | 277 | 2.0% | |
| Lutron | Grafik-Eye | GRX-3103-A-G | 277 | 5.0% | |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MACL-153M-WH | 120 | 5.0% | |
| Lutron | Diva | DVCL-153P | 120 | 3.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 14.0% | |
| Lutron | Ariadni | AYCL-153PH | 120 | 5.0% | |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

MODERN FORMS

| Forward Phase Dimmers (TRIAC) Cont. | | | | | |
|-------------------------------------|-----------|-------------|-----|-------|-----------------------|
| Lutron | Skylark | SCL-153P-WH | 120 | 3.0% | |
| Lutron | Maestro | MA-600-WH | 120 | N/A | Dimmer not responsive |
| Leviton | SureSlide | 6674-POW | 120 | 5.0% | |
| Lutron | Caseta | PD-6WCL | 120 | 2.0% | Flicker below 2% |
| Legrand | Harmony | HCL453PW | 120 | 5.0% | Flicker below 5% |
| Legrand | Radiant | RHCL453PW | 120 | 5.0% | Flicker below 5% |
| 0-10V Dimmers | | | | | |
| Lutron | Nova T | NTSTV | 120 | 9.0% | |
| Leviton | Decora | IP710-LFZ | 120 | 2.0% | |
| Control4 | Adaptive | C4-TV120277 | 120 | 1.0% | |
| Lutron | Diva | DVSTV | 120 | 2.0% | |
| Leviton | Renoir | AWSMT-7DW | 120 | 14.0% | |
| Legrand | Radiant | RH4FBL3PW | 120 | 1.0% | |
| Lutron | Nova T | NTSTV | 277 | 9.0% | |
| Leviton | Decora | IP710-LFZ | 277 | 3.0% | |
| Control4 | Adaptive | C4-TV120277 | 277 | 1.0% | |
| Lutron | Diva | DVSTV | 277 | 2.0% | |
| Legrand | Radiant | RH4FBL3PW | 277 | 1.0% | |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.