



145 West Commercial Ave. Moonachie, NJ 07074

chie, NJ 07074							
			Dimm	ner Compatibility	Guide		
			NOTE: Compatibility list is based upon testin	ng conducted by the manufacturer in a	lab simulated environment. Actual results	may vary.	
uct Family Name: Number:	Filaments: Fully Compatible 77652	-	4 776575	776600	776601		
ring Code:	LED5A19/27K/FIL			LED5G25/22K/FIL-NOS/2	LED5ST18/22K/FIL-NOS/2		
Number:	77660	02 77660	5 776609	776667			
ing Code:	LED5A19/22K/FIL-NOS			LED7ST18/27K/FIL/2			
-							
					Lamps per	Dimmer	
	Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes
ncandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)		IllumaTech	IPI06	Best	1	6	Dims down to 10%
	Leviton	SureSlide	6633-P	Best	1	6	Dims down to 10%
		Vizia Toggler	VPI06-1LZ TG-600	Good Best	1	6	2+ minimum load , minor flicker at LE 1-6 , dims down to 10% Dims down to 1%
		Diva	DV-600	Best	1	6	Dims down to 1%
	Lutron	Skylark	S-600	Best	1	6	Dims down to 1%
		Maestro	MAW-600	Good	1	6	2+ minimum load , dims down to 5%
		Titan	CD703-PW	Good	1	6	Flicker at LE with 1, dims down to 15%
	Legrand	Titan	CDLV703-PW	Good	1	6	Minor flicker at LE with 1 , dims down to 15%
		Harmony	D703-PTC	Good	1	6	Minor flicker Med to HE with 1 , dims down to 1%
		Harmony	H703-PTC	Good	1	6	Minor flicker at LE with 1 , dims down to 1%
		IllumaTech	IPL06	Best	1	6	Dims down to 1%
	Leviton	Sureslide	6674	Best	1	6	Dims down to 5%
		Decora	6672	Best	1	6	Dims down to 5%
		Diva	DVCL-153PL	Good	1	6	Shimmer at LE with 1-6 , dims down to 1%
		Toggler	TGCL-153PH	Good	1	6	Shimmer at LE with 1-6 , dims down to 1%
CFL/LED	Lutron	Maestro	MACL-153MLH	Good	1	6	Shimmer at LE with 1-6 , dims down to 10%
		Skylark	CTCL-153	Good	1	6	Shimmer at LE with 1-6, dims down to 1%
		Skylark Radio RA	SCL-153P RA2RR-6CL-PD	Good Good	1	6 6	Shimmer at LE with 1-6 , dims down to 1% Shimmer at LE with 1-6 , dims down to 1%
		Harmony	DCL453-PTC	Good	1	6	Shimmer at LE with 1-6 , dims down to 10%
	Legrand	Harmony	HCL453PTC	Good	1	6	Shimmer at LE with 1-6 , dims down to 10%
		Adorne Paddle	ADPD453LM2	Good	1	6	Dims down to 25%
Electronic Low Voltage		Vizia	VPE04	Best	1	6	Dims down to 10%
	Leviton	IllumaTech	IPE04	Good	1	6	Flicker at HE with 1, dims down to 5%
		Decora Skylark	6615-P SELVB-300P	Bad Good	1	<u> </u>	Flicker at HE with 1,dims down to 30% Flicker at HE with 1-3 , dims down to 10%
	Lutron	Skylark Countour	CTELV-303P	Good	1	6	Flicker at HE with 1, dims down to 10%
		Diva	DVELV-300P	Good	1	6	Flicker at HE with 1-2, dims down to 10%
		Maestro	MAELV-600	Good	1	6	Flicker at HE with 1 , dims down to 10%
		VIERTI	VTEL-600M-W	Best	1	6	Dims down to 10%
	Legrand	Scene Director	SCELV	Good	1	6	Dims down to 25%
Magentic Low Voltage		Vizia	VPM-06	Good	1	6	2+ minimum load , flicker at LE 1-6 , dims down to 10%
	Leviton	Decora	6613-P	Best	1	6	Dims down to 5%
	Lutron	Maestro	MALV-600	Bad	1	6	4+ minimum load , dims down to 15%
	Legrand	Harmony	DLV703-PW	Good	1	6	Minor flicker at MED to HE with 1 , dims down to 1%
			· · · ·				
Universal		Adorne SofTap	ADTP703TU	Best	1	6	Dims down to 10%
		Miro Decorator	DRD4-W	Not Compatible	1	6	Major flicker at Med with 1-6
	Legrand	Harmony		Best	1	6	Dims down to 15%
		Adorne Whisper Adorne Touch	ADWR700MMTUW2 ADTH700MMTUM2	Best Best	1	6	Dims down to 1% Dims down to 1%
		Decorator	DAL06P-C2-K-L	Good	1	6	Minor flicker at LE with 1-6 , dims down to 20%
	Cooper	Skye	SALO6P-W-K-L	Bad	1	6	Flicker at Med with 1 , minor flicker at LE with 2-6
aximum Tested (Lamps per Dimmer) ay experience "pop-on", lights cannot l e initially off. Then, the slider can be	be turned on immediately to th	th your dimmer system. For max neir minimum level. The slider ne	imum capacity please consult dimm eeds to be raised above the minimur	er manufacturer. m light level for the lights to fin	st turn on if they	0	
erall Rating	One or more of the following	ng observed: Major flickering	t various points, significant audib	ale noise, no dimming range	does not turn off		
Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off. One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.						
			•			en the slider (or other fo	rm of control button) is moved without affecting the light level
	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the periods of dead travel are minor and most of the time not visible. Minor audible noise.						
	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.						
End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.						
End (L.E.) Dead Travel	Determines now much, if a	ny, ueau travel exists at the to	p and bottom of the dimmer's ra	inge. Deau traver is when the	siluer call be moved without a	neung the light level.	
ct Information: te Industries Inc. test Commercial Avenue achie, New Jersey 07074 E: 1-800-528-5555 I-800-441-7708							
e Industries Inc. est Commercial Avenue achie, New Jersey 07074 E: 1-800-528-5555							