



ENERGY STAR

145 West Commercial Ave. Moonachie, NJ 07074

Moonachie, NJ 07074									
			Dimmer Co	mpatibility Guide					
		PLEASE	E: Compatibility list is based upon testing conducted		nvironment. Actual results ma	ay vary.			
roduct Family Name:	MRs Dimmable & Enclosed	Rated							
em Number:	771401 771402 771403 771403 771404								
ordering Code:	LED6PAR16GUNF25/60/82	7/D LED6PAR16GUFL35/60/8	27/D LED6PAR16GUNF25/60/830/D	LED6PAR16GUFL35/60/83	0/D				
Lamps per Dimmer									
	Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes		
	Leviton	IllumaTech	IP106	Good	1	6	Minor flickering at 10-20% with 1-3 , dims down to 10%		
		Sureslide	6633-P	Good	1	6	Minor flickering at 10-20% with 1-3 , dims down to 10%		
		Vizia	VPI06-1LZ	Not Compatible	1	6	Does not turn off 1-6		
		Toggler	TG-600	Good	1	6	Minor flickering at 1-20% with 1-6 , dims down to 1%		
Incandescent/Halogen	Lutron	Diva	DV-600	Good	1	6	Minor flickering at 25% with 1-6 , dims down to 1%		
(Triac/Phase	Editori	Skylark	S-600	Good	1	6	Minor flickering at 1-20% with 1-6 , dims down to 1%		
ut/Leading Edge Dimmers)		Maestro	MAW-600	Bad	1	6	5+ minimum load ,dims down to 5% 5-6		
		Titan	CD703-PW	Good	1	6	Minor flickering at 10-20% with 1-3 , dims down to 10%		
	Legrand	Harmony	D703-PTC	Good	1	6	Minor flickering at 10-20% with 1-5 , dims down to 10%		
	Legiana	Harmony	H703-PTC	Good	1	6	Minor flickering at 1-20% , dims down to 1%2-6		
		Titan	CDLV703-PW	Good	1	6	Minor flickering 30% , dims down to 1%2-6		
		IllumaTech	IPL06	Best	1	6	Dims down to 10% with 1-2 and 1% with 3-6		
	Leviton	Sureslide	6674	Best	1	6	Dims down to 10% with 1 and 2% with 2-6		
		Decora	6672	Best	1	6	Dims down to 10% with 1 and 2% with 2-6		
		Diva	DVCL-153PL	Bad	1	6	Minor flickering 0-50% with 1-6		
	Lutron	Toggler	TGCL-153PH	Bad	1	6	Minor flickering 0-50% with 1-6		
CFL/LED		Maestro	MACL-153MLH	Bad	1	6	Minor flickering 0-50% with 1-6		
		Skylark	CTCL-153	Bad	1	6	Minor flickering 0-50% with 1-6		
		Skylark	SCL-153P	Bad	1	6	Minor flickering 0-50% with 1-6		
		Radio RA	RA2RR-6CL-PD	Good	1	6	Minor flickering at 10-20% with 1-6 , dims down to 10%		
	Legrand	Harmony	DCL453-PTC	Bad	1	6	Minor flickering 0-50% with 1-6		
		Harmony	HCL453PTC	Bad	1	6	Flickering at Medium & HE with 1-6		
		Adorne Paddle	ADPD453LM2	Bad	1	6	Flickering at LE & Medium with 1-6		
		Vizia	VPE04	Good	1	6	Minor flickering at 10-30% with 1-6, dims down to 10%		
	Leviton	IllumaTech	IPE04	Bad	1	6	Minor flickering at 5-40% with 1-6, dims down to 5%		
		Decora	6615-P	Bad	1	6	Minor flickering at 25-30% with 1-6, dims down to 25%		
		Skylark	SELVB-300P	Good	1	6	Minor flickering at 10-20% with 1-6, dims down to 10%		
Electronic Low Voltage	Lutron	Skylark Countour	CTELV-303P	Good	1	6	Minor flickering at 10-20% with 1-6, dims down to 10%		
-		Diva	DVELV-300P	Good	1	6	Minor flickering at 10-20% with 1-6, dims down to 10%		
		Maestro	MAELV-600	Good	1	6	Minor flickering at 10-20% with 1-6, dims down to 10%		
		VIERTI	VTEL-600M-W	Best	1	6	Dims down to 8% with 1-6		
	Legrand	Scene Director	SCELV	Good	1	6	Dims down to 20% with 1-6		
						~			
	Leviton	Vizia	VPM-06	Not Compatible	1	6	Doesn't turn on with 1-6		
Magentic Low Voltage		Decora	6613-P	Good	1	6	Minor flickering at 10% with 1-6, dims down to 10%		
	Lutron	Maestro	MALV-600	Not Compatible	1	6	Doesn't turn on with 1-6		
	Legrand	Harmony	DLV703-PW	Good	1	6	Minor flickering at 5% with 1 and 1% with 2-6		
						2			
		Adorne SofTap	ADTP703TU	Best	1	6	Dims down to 15% with 1-6		
		Miro Decorator	DRD4-W	Not Compatible	1	6	Strobe at LE with 1-6		
	Legrand	Harmony	H703PTUTC	Best	1	6	Dims down to 15% with 1-6		

	Legiallu	паппопу	H/USPIUIC	Best	1	0	
Universal		Adorne Whisper	ADWR700MMTUW2	Best	1	6	Dims down to 1% with 1-6
		Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims down to 1% with 1-6
	Cooper	Decorator	DAL06P-C2-K-L	Good	1	6	Dims 25% with 1-6
	Cooper	Skye	SAL06P-W-K-L	Bad	1	6	Flickering 5-25% with 1-6

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

[†]May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they

were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating						
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.					
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.					
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the					
	light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.					
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.					
High End (H.E.) Dead Travel	Determines how much if any dead travel evicts at the ten and bettern of the dimmer's range. Dead travel is when the slider can be moved without effecting the light level					
Low End (L.E.) Dead Travel	- Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.					
Contact Information:						
Bulbrite Industries Inc.						
145 West Commercial Avenue						
Moonachie, New Jersey 07074 PHONE: 1-800-528-5555						
FAX: 1-800-441-7708						
Email: ProductSupport@bulbrite.com						
©2017 Bulbrite Industries Inc.						
All Rights Reserved.						