



PRODUCTS

WEBINARS

RESOURCES

GALLERY

ABOUT

WHERE TO BUY






Power Supply Comparison Charts

- ELV
- 0-10
- DMX
- 2XK TUNABLE WHITE
- LUTRON HI-LUME®
- LUTRON HI-LUME® TUNABLE WHITE
- UNI POWER SUPPLIES
- UNI POWER SUPPLIES TUNABLE WHITE

Dynamic/Tunable White uses one or two power supplies, dependent on the controller or dimmer(s) used.
Lutron Hi-Lume® can be used in both single or dual power formats, dependent on the controller or dimmer(s).

INDOOR CONSTANT VOLTAGE REMOTE POWER SUPPLIES 24VDC, LUTRON ECOSYSTEM

[Download PDF](#)

| LUTRON HI-LUME® PREMIER .1% ECOSYSTEM®† | | | |
|---|--|---|---|
| ORDERING CODES | L3D0-96W24V-U  | 2-WIRE ECOSYSTEM LTEA4U1UKL-CV240  | 3-WIRE ECOSYSTEM L3DA4U1UKL-CV240  |
| SPECIFICATIONS | | | |
| MAXIMUM LOAD | 96W | 5W-40W | 5W-40W |
| INPUT VOLTAGE | 120-277VAC | 120-277VAC | 120-277VAC |
| OUTPUT VOLTAGE | 24VDC | 24VDC | 24VDC |
| DIMENSIONS | 10.5" X 5.5" X 2" | 4" X 4.89" X 2.62" | 4" X 4.89" X 2.62" |
| CLASSIFICATION | CLASS 2 | CLASS 2 | CLASS 2 |
| DIMMING AND CONTROLS | | | |
| RADIO RA2 | • | • | • |
| HOMEWORKS QS | • | • | • |
| PHPM-3F-120 | • | • | • |
| PHPM-3F-DV | • | • | • |
| BCI-0-10 | • | • | • |

*Tunable White Color Temperature is compatible with 0-10V, ELV, DMX, and Lutron Hi-Lume® Power Supplies.

PRODUCTS

- Recessed
- Ceiling
- Suspension

RESOURCES

- Catalog
- Price List
- Downloads

GALLERY

- Images
- Videos
- Video Downloads

ABOUT

- Mission
- Awards & Recognition
- Webinars

WHERE TO BUY

- Sales Map
- Contact Us

JOIN OUR MAILING LIST

Email SIGN UP