








## Power Supply Comparison Charts

- ELV
- 0-10
- DMX
- 2XK TUNABLE WHITE
- LUTRON HI-LUME®
- LUTRON HI-LUME® TUNABLE WHITE
- UNI POWER SUPPLIES
- UNI POWER SUPPLIES TUNABLE WHITE

P

**DYNAMIC/TUNABLE WHITE CONTROLLER AND POWER SUPPLIES 24VDC INDOOR CONSTANT VOLTAGE POWER SUPPLIES WITH DMX DRIVERS**  
 Download PDF

DYNAMIC COLOR CHANGING (DMX) POWER SUPPLIES & RECOMMENDED CONTROLLERS†				
ORDERING CODES	PSB-100W-24VDC-2XK 	PSB-2X100W-24VDC-2XK 	PSB-3X100W-24VDC-2XK 	PSB-4X100W-24VDC-2XK 
SPECIFICATIONS				
MAXIMUM LOAD OF LED STRIP LENGTH	100W 5 WATTS - 20FT MAX. 10 WATTS - 10FT MAX.	2X100W 5 WATTS 2 X 20FT MAX. 10 WATTS - 2 X 10FT MAX.	3X100W 5 WATTS 3 X 20FT MAX. 10 WATTS - 3 X 10FT MAX.	4X100W 5 WATTS 4 X 20FT MAX. 10 WATTS - 4 X 10FT MAX.
INPUT VOLTAGE	120-277VAC	120-277VAC	120-277VAC	120-277VAC
OUTPUT VOLTAGE	24VDC	24VDC	24VDC	24VDC
DIMENSIONS	12.14" X 6.48" X 2.18"	14" X 10" X 3"	17" X 10" X 3"	17" X 10" X 3"
CLASSIFICATION	CLASS 2	CLASS 2	CLASS 2	CLASS 2
IN WALL MOUNTING	PSB-100W-24VDC-2XK-IW	NA	NA	NA
DMX DYNAMIC/TUNABLE WHITE DIMMING & CONTROLS				
TUNABLE WHITE TOUCH CONTROLLER (CDMX1-2XK)	•	•	•	•
<ul style="list-style-type: none"> <li>Flicker free dimming</li> <li>Aluminum casing for optimal heat dissipation</li> <li>Isolated output power per NEC and UL safety requirements</li> <li>UL &amp; ETL recognized/ listed, meets UL 8750, 1310 requirements</li> </ul>		<ul style="list-style-type: none"> <li>Auto-reset; short circuit, overload and thermal protection</li> <li>Class 2 power supply</li> <li>Efficient, High power factor &gt; 0.90</li> </ul>		
 <p><b>8.5 x 14 inch In-Wall Mounting Kit:</b> Includes power supply, box cover and stud hangers for installing Junction Box in wall. Select "IW" in the options section of compatible power supply ordering codes if an In-Wall Mounting Kit is needed.</p> <p><b>Ordering Codes:</b> PSB-100W-24VDC-2XK-IW</p>				