Q



PRODUCTS

WEBINARS

RESOURCES GALLERY

WHERE TO BUY

ABOUT

Power Supply Comparison Charts

ELV	0-10	DMX	2XK TUNABLE WHITE	LUTRON HI-LUME®	LUTRON HI-LUME® TUNABLE WHITE	UNI POWER SUPPLIES	UNI POWER SUPPLIES TUNABLE WHITE	Ρ
							D.	

UNI INDOOR CONSTANT VOLTAGE REMOTE POWER SUPPLIES - 24VDC UNIVERSAL DIMMING WITH ELV, 0-10V, TRIAC | DYNAMIC TUNABLE WHITE TECHNOLOGY Download PDF

	UNIVERSAL POWE	R SUPPLIES & COMPATIBLE DIMME	RS†	
ORDERING CODES	PSB-2X40W-UNI-24VDC	PSB-2X60W-UNI-24VDC	PSB-2X96W-UNI-24VDC	PSB-4X96W-UNI-24VDC
		SPECIFICATIONS	1	I
MAXIMUM LOAD	2X40W	2X60W	2X96W	4X96W
INPUT VOLTAGE	120-277VAC	120-277VAC	120-277VAC	120-277VAC
OUTPUT VOLTAGE	24VDC	24VDC	24VDC	24VDC
DIMENSIONS	12.15" X 6.48" X 2.18	12.15" X 6.48" X 2.18"	12.15" X 6.48" X 2.18"	17" X 13" X 3"
CLASSIFICATION	CLASS 2	CLASS 2	CLASS 2	CLASS 2
IN-WALL MOUNTING	PSB-2X40W-UNI-24VDC-IW	PSB-2X60W-UNI-24VDC-IW	PSB-2X96W-UNI-24VDC-IW	N/A
	ELV	DIMMING & CONTROLS		
LUTRON DIVA: DVELV-300P	•	•	•	•
LUTRON SKYLARK: SELV-300P	•	•	•	•
LUTRON RADIO RA2: RRD-6NA	•	•	•	•
LUTRON MAESTRO: MAELV-600	•	•	•	•
LEGRAND ADORNE: ADTP-703TUM4	•	•	•	•
	0-10	DIMMING & CONTROLS		•
PHILIPS SUNRISE: SR1200ZTUNV	•	•	•	•
LUTRON DIVA: DVTV-WH, DVSTV-WH	•	•	•	•
LUTRON NOVA T: NTSTV-DV-XX	•	•	•	•
LUTRON GRAFIX EYE QS: QSGRJ-XP	•	•	•	•
LUTRON RADIO RA2: RRD-10ND	•	•	•	•
LEVITON: LEV40050	•	•	•	•
LEVITON IP710-LFZ	•	•	•	•
LEGRAND: ADPD4FBL3P2W4	•	•	•	•
	TRIA	C DIMMING & CONTROLS		
LUTRON SKYLARK: S2-L-WH	•	•	•	•

https://www.pureedgelighting.com/edge/about/power_supply_comparison_chart.php?1603202508140#!tab=tab8

PureEdge Lighting - Power Supply Comparision Chart

		1	1				
LUTRON DVLV-600P-WH	•	•					
LUTRON DVLV-603P-WH	•	•	•	•			
LUTRON MALV-600-WH	•	•	•	•			
LUTRON MALV-1000-WH	•	•	•	•			
LUTRON MA-R-XX	•	•	•	•			
 Flicker free dimming Aluminum casing for optimal heat dissipation Isolated output power per NEC and UL safety requirements UL & ETL recognized/ listed, meets UL 8750, 1310 requirements Auto-reset; short circuit, overload and thermal protection Class 2 power supply Efficient, High power factor > 0.90 The Solid State Constant Voltage Uni-Power Supply is compatible with most commercially available Dimmers: The Solid State Constant Voltage Uni-Power Supply is compatible with most commercially available Dimmers: Triac Dimmer : (Forward Phase) Typically used for the dimming of Incandescent and Low Voltage Magnetic Transformers ELV Dimmer : (Reverse Phase) Dimming of Electronic Low Voltage Transformers and Power Supply's used for LED lighting 0-10 Dimmer : Dims the Low Voltage side of a 0-10 volt power supply commonly used in large scale lighting or commercial applications. The Uni-Power Supply is recommended with any Siemens/Murray brand of arc fault breaker to overcome the issues with tripping the breakers with an ELV LED Low Voltage Drivers. 							

PRODUCTS	RESOURCES	GALLERY	ABOUT	WHERE TO BUY	JOIN OUR MAILING LIST
Recessed	Catalog	Images	Mission	Sales Map	Email SIGN UP
Ceiling	Price List	Videos	Awards & Recognition	Contact Us	
Suspension	Downloads	Video Downloads	Webinars		f y 🖗 🖸 🛱
LED Strips & Linear Extrusions	Warranty		Careers		
Wall	Terms & Conditions		Contact Us		
Cabinet/Shelf Lighting	Events				
Floor	Other Resources				
Outdoor					
Power Supplies & Controllers					
Accessories & Lamps					

© PureEdge Lighting 2020 | 1718 Fullerton Ave | Chicago, Illinois 60614 | Phone: 773.770.1195 | Fax: 773.935.5613 | info@PureEdgeLighting.com