



145 West Commercial Ave.
Moonachie, NJ 07074

Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

Product Family Name:	GRAND LED FILAMENT						
Item Number:	776300	776301	776302	776303			
Ordering Code:	LED4PS52/22K/FIL	LED4ET25/22K/FIL	LED4G63/22K/FIL	LED4WB/22K/FIL			
Item Number:	776304	776305	776306	776314			
Ordering Code:	LED4BH/22K/FIL	LED4DIA/22K/FIL	LED4OLIVE/22K/FIL	LED4BT56/22K/FIL	Lamps per Dimmer		
	Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	IllumaTech	IPI06	Best	1	6	Dims down to 5% with 1-6
		SureSlide	6633-P	Best	1	6	Dims down to 5% with 1-6
		Vizia	VPI06-1LZ	Good	1	6	Dims down to 5% with 1-6, Minor flicker at Med with 1
	Lutron	Toggle	TG-600	Best	1	6	Dims down to 5% with 1-6
		Diva	DV-600	Best	1	6	Dims down to 5% with 1-6
		Skylark	S-600	Best	1	6	Dims down to 5% with 1-6
		Maestro	MAW-600	Good	2	6	Dims down to 5% with 2-6, shimmer at LE with 1-3
	Legrand	Titan	CD703-PW	Good	1	6	Dims down to 3% with 1-6, minor flicker at Med with 1-2
		Harmony	D703-PTC	Good	1	6	Dims down to 3% with 1-6, minor flicker at Med with 1-2
		Harmony	H703-PTC	Good	1	6	Dims down to 3% with 1-6, minor flicker at Med with 1
CFL/LED	Leviton	IllumaTech	IPL06	Best	1	6	Dims down to 0.2% with 1-6
		SureSlide	6674	Best	1	6	Dims down to 10% with 1-6
		Decora	6672	Best	1	6	Dims down to 10G% with 1-6
	Lutron	Skylark	CTCL-153	Best	1	6	Dims down to 0.1% with 1-6
		Diva	DVCL-153PL	Best	1	6	Dims down to 0.1% with 1-6
		Maestro	MAEL-153MLH	Best	1	6	Dims down to 7% with 1-6
		Skylark	SCL-153P	Best	1	6	Dims down to 0.1% with 1-6
		Toggle	TGCL-153PH	Best	1	6	Dims down to 0.1% with 1-6
		Radio RA	RA2RR-6CL-PD	Best	1	6	Dims down to 5% with 1-6
	Legrand	Harmony	DCL453-PTC	Best	1	6	Dims down to 7% with 1-6
		Harmony	HCL453PTC	Best	1	6	Dims down to 9% with 1-6
		Adorne Paddle	ADPD453LM2	Good	1	6	Dims down to 25% with 1-6
Electronic Low Voltage	Leviton	Vizia	VPE04	Good	1	6	Dims down to 13% with 1-6, minor flicker at Med with 1-6
		IllumaTech	IPE04	Good	1	6	Dims down to 10% with 1-6, minor flicker at Med with 1-6
		Decora	6615-P	Bad	1	6	dims down to 35% with 1-6,
	Lutron	Skylark Countour	CTELV-303P	Good	1	6	Dims down to 10% with 1-6, minor flicker at Med with 1-6
		Diva	DVELV-300P	Good	1	6	Dims down to 8% with 1-6, minor flicker at Med with 1-6
		Maestro	MAELV-600	Good	1	6	Dims down to 10% with 1-6, minor flicker at Med with 1-6
		Skylark	SELVB-300P	Good	1	6	Dims down to 10% with 1-6, minor flicker at Med with 1-6
		VIERTI	VTCL-600M-W	Best	1	6	Dims down to 10% with 1-6,
	Legrand	Scene Director	SCELV	Good	1	6	Dims down to 25% with 1-6
	Magentic Low Voltage	Leviton	Vizia	VPM-06	Good	2	6
Decora			6613-P	Best	1	6	Dims down to 10% with 1-6
Lutron		Maestro	MALV-600	Good	2	6	Dims down to 7% with 1-6,
		Harmony	DLV703-PW	Good	1	6	Dims down to 3% with 1-6, minor flicker at Med with 1
Legrand		Titan	CDLV703-PW	Good	1	6	Dims down to 3% with 1-6, minor flicker at Med with 1
Universal	Legrand	Adorne SoftTap	ADTP703TU	Best	1	6	Dims down to 12% with 1-6
		Miro Decorator	DRD4-W	Best	1	6	Dims down to 3% with 1-6
		Harmony	H703PTUTC	Best	1	6	Dims down to 12% with 1-6
		Adorne Whisper	ADWR700MMTUW2	Best	1	6	Dims down to 0.1% with 1-6
		Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims down to 0.1% with 1-6
	Cooper	Decorator	DAL06P-C2-K-L	Good	1	6	Dims down to 11% with 1-6, minor flicker at Med with 1
		Skye	SAL06P-W-K-L	Good	1	6	Dims down to 0.5% with 1-6, shimmer at LE with 1

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.
 †May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
Low End (L.E.) Dead Travel	

Contact Information:
 Bulbrite Industries Inc.
 145 West Commercial Avenue
 Moonachie, New Jersey 07074
 PHONE: 1-800-528-5555
 FAX: 1-800-441-7708
 Email: ProductSupport@bulbrite.com
 ©2017 Bulbrite Industries Inc.
 All Rights Reserved.