



145 West Commercial Ave. Mansfield, NJ 07034

### Dimmer Compatibility Guide

PLEASE NOTE: Compatibility for a lamp type depends on the dimmer model & the lamp manufacturer. Actual results may vary.

<b>Product Family Name:</b>	776775	776883	776897	776878
<b>Item Number:</b>	LED8625/27K/FL/3	LED8640/27K/FL/M/3	LED8640/27K/FL/M/3	LED8640/27K/FL/3
<b>Ordering Code:</b>				

Dimmer Type	Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes
					Recommended Minimum	Maximum (EULI)*	
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	BulmaTech	IP06	Best	1	6	Dimm down to 18%
		SlideSlide	6633-P	Best	1	6	Dimm down to 2%
		Viva	VPI06-L12	Good	2	6	Dimm down to 7%
		Toggle	TIC-600	Best	1	6	Dimm down to 10%
		Diva	DV-600	Best	1	6	Dimm down to 1%
		DayLink	S-600	Best	1	6	Dimm down to 1%
	Legrand	Manitou	MAN6-600	Best	2	6	Dimm down to 6%
		Titan	CD703-PPW	Best	1	6	Dimm down to 20%
		Harmony	D703-PTC	Best	1	6	Dimm down to 1%
		Harmony	HD03-PTC	Best	1	6	Dimm down to 3%
CFL/LED	Leviton	BulmaTech	PL06	Best	1	6	Dimm down to 2%
		Controlite	6674	Best	1	6	Dimm down to 10%
		Decora	6672	Best	1	6	Dimm down to 8%
		Decora Slide	DS06-L12	Best	1	6	Dimm down to 10%
		DayLink	CTL0-LS3	Best	1	6	Dimm down to 8%
		Day	DVCL-LS3M	Best	1	6	Dimm down to 1%
	Lutron	Manitou	MANCL-LS3M/3W	Best	1	6	Dimm down to 7%
		DayLink	SCL-LS3P	Best	1	6	Dimm down to 1%
		Toggle	TCL0-LS3M	Best	1	6	Dimm down to 1%
		Radio RA	RA288-CL-PO	Best	1	6	Dimm down to 5%
		Harmony	DCL433-PTC	Best	1	6	Dimm down to 7%
		Harmony	HCL433-PTC	Best	1	6	Dimm down to 13%
Electronic Low Voltage	Leviton	Viva	VPI04	Best	1	6	Dimm down to 13%
		BulmaTech	IP04	Best	1	6	Dimm down to 10%
		Decora	6615-P	Best	1	6	Dimm down to 42%
		DayLink Countour	CTL0-3ESP	Best	1	6	Dimm down to 10%
		Day	DVCLV-3ESP	Best	1	6	Dimm down to 1%
		Manitou	MANCLV-600	Best	1	6	Dimm down to 10%
	Legrand	DayLink	SELV-300P	Best	1	6	Dimm down to 10%
		VITE	VITE-300M-3W	Best	2	6	Dimm down to 20%
		Scene Director	SECLV	Best	1	6	Dimm down to 27%
Magnetic Low Voltage	Leviton	Day	VMV-06	Best	2	6	Dimm down to 9%
		Decora	6613-P	Best	1	6	Dimm down to 4%
		Manitou	MANLV-600	Best	2	6	Dimm down to 7%
	Legrand	Harmony	DLV703-PPW	Best	1	6	Dimm down to 1%
		Harmony	DLV703-PPW	Best	1	6	Dimm down to 20%
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDM15-BL2	Best	1	6	Dimm down to 18%
		Decora Smart & Smart Technology	DDM15	Best	1	6	Dimm down to 15%
		Decora Wireless smart dimmer Wi-Fi	PD-SDM15	Best	1	6	Dimm down to 15%
		Decora Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dimm down to 7%
		Decora Touch Wi-Fi Tri Universal	ADT700MAMFLM2	Best	1	6	
		Decora Soft Tap Wi-Fi Tri Universal	ADT700MFLM2	Best	1	6	
Universal	Legrand	Adorne Saffron	ADT701SL1	Good	1	6	Dimm down to 24%
		Adorne Decora	DR04-WF	Good	1	6	Dimm down to 2%, dimmer at LE with 1-6
		Harmony	HT03PFLTC	Good	1	6	Dimm down to 28%
		Adorne Bridge	ADT700MAMFLM2	Best	1	6	Dimm down to 2%
		Adorne Touch	ADT700MAMFLM2	Best	1	6	Dimm down to 3%
		Cooper	DA00P-C2-K-L	Good	1	6	Dimm down to 1%, minor flicker at LE with 1-6
	Day	DA00P-W-E-L	Good	1	6	Dimm down to 1%, minor flicker at LE with 1-6	

\*Maximum Tested Lamps per Dimmer. Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

\*May experience "pop on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

<b>Overall Rating</b>	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
<b>Not Compatible</b>	One or more of the following observed: Major flickering observed at various points, audible noise may be present, dimming not smooth.
<b>Good</b>	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
<b>Best</b>	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dba), wide dimming range, cut dim down to 20% or less of light output.
<b>High End (H.E.) Dead Travel</b>	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
<b>Low End (L.E.) Dead Travel</b>	

©2019 Bulbrite Industries Inc.  
 145 West Commercial Avenue, Mansfield, NJ 07034  
 PHONE: 1-800-528-5555 FAX: 1-800-443-7708  
 Email: [productsupport@bulbrite.com](mailto:productsupport@bulbrite.com)  
 ©2019 Bulbrite Industries Inc.  
 All Rights Reserved.