

Product Family: 3.5" Oculux Architectural

Sku Tested: R3CRN-11

Related Model Numbers: R3CRN-11, R3CSN-11

Test Voltage: 120~277V

Control Type: ELV, TRIAC, 0-10V

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|-------------------|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 2.0% | |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 0.4% | |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | 0.4% | |
| Legrand | Radiant | RH703PTUW | 120 | 3.0% | |
| Legrand | Adorne (ELV) | ADTP703TUW4 | 120 | 3.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUW4 | 120 | 0.2% | |
| Cooper | AL Series | AAL06 | 120 | 4.0% | |
| Control4 | Adaptive | C4-APD277 | 277 | 3.0% | |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 0.8% | |
| Lutron | Diva | DVELV-300P | 120 | 0.3% | |
| Lutron | Maestro | MAELV-600 | 120 | 0.9% | |
| Lutron | Skylark | SELV-300P | 120 | 0.6% | |
| Leviton | Illumatech | IPE04-1LZ | 120 | 9.0% | |
| Lutron | Maestro | RRD-6NA | 120 | 2.0% | |
| Leviton | SureSlide | 6615-P0W | 120 | 4.0% | |
| Leviton | Decora | DSE06-10Z | 120 | 1.0% | |
| Lutron | Caseta | PD-5NE | 120 | 0.8% | |
| Lutron | Homeworks | HRD-5NE | 120 | 0.9% | |
| Leviton | Renoir II | AWSMT-EBW | 120 | 0.9% | |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 0.9% | |
| Leviton | Renoir II | AWSMT-EBW | 277 | 0.9% | |
| Lutron | Grafik-Eye | GRX-3103-A-G | 277 | 0.9% | |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MACL-153M-WH | 120 | 0.9% | |
| Lutron | Diva | DVCL-153PD | 120 | 1.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 28.0% | Flicker below 28% |
| Lutron | Ariadni | AYCL-153PH | 120 | 1.0% | |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.

WAC LIGHTING
Responsible Lighting®

| Forward Phase Dimmers (TRIAC) Cont. | | | | | |
|-------------------------------------|-----------|-------------|-----|-------|--|
| Lutron | Skylark | SCL-153P-WH | 120 | 1.0% | |
| Lutron | Maestro | MA-600-WH | 120 | N/A | Dimmer not responsive |
| Leviton | SureSlide | 6674-POW | 120 | 1.0% | |
| Lutron | Caseta | PD-6WCL | 120 | 0.6% | |
| Legrand | Harmony | HCL453PW | 120 | 3.0% | Flicker below 3% |
| Legrand | Radiant | RHCL453PW | 120 | 22.0% | Flicker below 22% |
| 0-10V Dimmers | | | | | |
| Lutron | Nova T | NTSTV | 120 | 3.0% | |
| Leviton | Decora | IP710-LFZ | 120 | 3.0% | |
| Control4 | Adaptive | C4-TV120277 | 120 | 3.0% | |
| Lutron | Diva | DVSTV | 120 | 3.0% | There is still output when dimmer is off |
| Leviton | Renoir | AWSMT-7DW | 120 | 3.0% | |
| Legrand | Radiant | RH4FBL3PW | 120 | 3.0% | |
| Lutron | Nova T | NTSTV | 277 | 3.0% | |
| Leviton | Decora | IP710-LFZ | 277 | 3.0% | |
| Control4 | Adaptive | C4-TV120277 | 277 | 3.0% | |
| Lutron | Diva | DVSTV | 277 | 3.0% | |
| Leviton | Renoir | AWSMT-7DW | 277 | 8.0% | Flicker below 8% |
| Legrand | Radiant | RH4FBL3PW | 277 | 8.0% | Flicker below 8% |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@waclighting.com.