

ARDITO 3-1/2" & 4"

READV1 Performance 1 / ELV
Lumileds Luxeon COB 1205
ERP ESS015W-0350-42

CONTRASTE**DIMMING INFORMATION**

- Dimmers used: ELV only
- Audible noise: None
- Number of units tested: 1 to 10

Company	Models	Codes	Types	Dimming Performances		
				Programmable	Dimming Range *	Optimal Performance **
LUTRON DISCONTINUED	SKYLARK ***	SELV-300P	ELV	NA	7% - 100%	6% - 100%
	DIVA ***	DVELV-300P	ELV	NA	7% - 100%	6% - 100%
	NOVA T	NTELV-600	ELV	NA	14% - 100%	22% - 100%
	RADIO RA2	RRD-6NA-WH	ELV	YES	2% - 100%	12% - 100%
	MAESTRO	MAELV-600 Slider	ELV	NA	11% - 100%	11% - 100%
	MAESTRO	MAELV-600 Pull Tab	ELV	YES	2% - 100%	9% - 100%
	MAESTRO ***	MRF2-6ELV-120	ELV	YES	2% - 100%	7% - 100%
	GRAFIK T	GTJ-5NEM	ELV	YES	9% - 100%	9% - 100%
LEVITON	SPACER SYSTEM	SPSELV-600	ELV	NA	12% - 100%	12% - 100%
	DECORA	DSE06-10Z	ELV	NA	5% - 100%	10% - 100%
	DECORA	IPE04-LAW	ELV	YES	23% - 100%	23% - 100%
	RENOIR II	AWSMT-EAW	ELV	NA	0% - 100%	7% - 100%
	RENOIR II	AWSMG-EB	ELV	NA	0% - 100%	7% - 100%
	VIZIA +	VPE06-1LZ	ELV	YES	1% - 100%	7% - 100%
	VIZIA	IPE04-1LZ	ELV	YES	5% - 100%	11% - 100%
	DECORA	6615-P	ELV	YES	13% - 100%	13% - 100%
LEGRAND	VISIA RF +	VRE06-1LZ	ELV	YES	12% - 100%	12% - 100%
	PASS & SEYMOUR	H703PTUTC Min 6W	ELV	Auto	15% - 100%	15% - 100%

* Full Dimming Range

** Optimal Performance: Dimming range for ideal synchronized startup conditions

*** The % may vary depending on the number of luminaire used

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

CONTRASTE

ARDITO 3-1/2" & 4"

READV1 Performance 1 / 0-10V

Lumileds Luxeon COB 1205

ERP ESS015W-0350-42

CONTRASTE

DIMMING INFORMATION

- Dimmers used: 0-10V
- Audible noise: None
- Number of units tested: 1 to 10

Company	Models	Codes	Types	Dimming Performances		
				Programmable	Dimming Range *	Optimal Performance **
LUTRON	DIVA	DVTV	0-10V	NA	8% - 100%	22% - 100%
	MAESTRO	MS-Z101-WH	0-10V	YES	12% - 100%	24% - 100%
	NOVA T	NTSTV-DV	0-10V	NA	12% - 100%	17% - 100%
LEVITON	ILLUMATECH	IP710-LFZ	0-10V	NA	8% - 100%	11% - 100%
	ILLUMATECH	IP710-DLZ	0-10V	NA	8% - 100%	22% - 100%
	RENOIR II	AWSWG-7DW	0-10V	NA	19% - 100%	22% - 100%

* Full Dimming Range

** Optimal Performance: Dimming range for ideal synchronized startup conditions

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

CONTRASTE

ARDITO 3-1/2" & 4"

Performance 2 / ELV
 Lumileds Luxeon COB 1205
 ERP ESS030W-0550-42

CONTRASTE**DIMMING INFORMATION**

- Dimmers used: ELV only
- Audible noise: None
- Number of units tested: 1 to 10

Company	Models	Codes	Types	Dimming Performances		
				Programmable	Dimming Range *	Optimal Performance **
LUTRON	SKYLARK	SELV-300P	ELV	NA	8% - 100%	8% - 100%
	DIVA	DVELV-300P	ELV	NA	8% - 100%	10% - 100%
	RADIO RA2	RRD-6NA-WH	ELV	YES	3% - 100%	7% - 100%
	MAESTRO ***	MAELV-600 Slider	ELV	NA	21% - 100%	12% - 100%
	GRAFIK T	GTJ-5NEM	ELV	YES	11% - 100%	11% - 100%
	SPACER SYSTEM	SPSELV-600	ELV	NA	13% - 100%	13% - 100%
LEVITON	VIZIA	IPE04-1LZ	ELV	YES	24% - 100%	24% - 100%
	DECORA	6615-P	ELV	YES	13% - 100%	16% - 100%
	VISIA RF +	VRE06-1LZ	ELV	YES	13% - 100%	25% - 100%
	DECORA	DSE06-10Z	ELV	NA	6% - 100%	13% - 100%
	DECORA	IPE04-LAW	ELV	YES	6% - 100%	16% - 100%
	RENOIR II	AWSMT-EAW	ELV	NA	0% - 100%	16% - 100%
	RENOIR II	AWSMG-EB	ELV	NA	0% - 100%	16% - 100%
COOPER	SKEY AL	SAL06P	ELV	YES	3% - 100%	0% - 100%
	ASPIRE RF	RF9540-NDW	ELV	YES	27% - 100%	0% - 100%
LEGRAND	PASS & SEYMOUR	H703PTUTC Min 6W	ELV	Auto	18% - 100%	18% - 100%

* Full Dimming Range

** Optimal Performance: Dimming range for ideal synchronized startup conditions

*** The % may vary depending on the number of luminaire used

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

CONTRASTE

ARDITO 3-1/2" & 4"

Performance 2 / 0-10V
Lumileds Luxeon COB 1205
ERP ESS030W-0550-42

CONTRASTE

DIMMING INFORMATION

- Dimmers used: 0-10V
- Audible noise: None
- Number of units tested: 1 to 10

Company	Models	Codes	Types	Dimming Performances		
				Programmable	Dimming Range *	Optimal Performance **
LEVITON	ILLUMATECH	IP710-LFZ	0-10V	NA	23% - 100%	35% - 100%
	RENOIR II	AWSWG-7DW	0-10V	NA	23% - 100%	35% - 100%

* Full Dimming Range

** Optimal Performance: Dimming range for ideal synchronized startup conditions

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

CONTRASTE