



145 West Commercial Ave.
Moonachie, NJ 07074

Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

Product Family Name: Globe Title 24 Compliant: JAB
Item Number: 774137
Ordering Code: LED8G25/930/S/F/D

	Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes
					Recommended Minimum	Maximum Tested*	
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	IlumaTech	IP106	Good	1	6	Dims down to 12%
		SureSlide	6633-P	Best	1	6	Dims down to 5%
	Lutron	Vizia	VPI06-1LZ	Good	2	6	Dims down to 9%, 2 minimum load without ghost
		Toggler	TG-600	Good	1	6	Dims down to 12%
		Diva	DV-600	Best	1	6	Dims down to 2%
		Skylark	S-600	Best	1	6	Dims down to 4%
		Maestro	MAW-600	Good	2	6	Dims down to 10%, 2 minimum load without ghost
		Titan	CD703-PW	Good	1	6	Dims down to 13%
	Legrand	Harmony	D703-PTC	Best	1	6	Dims down to 2%
		Harmony	H703-PTC	Best	1	6	Dims down to 5%
CFL/LED	Leviton	IlumaTech	IP106	Best	1	6	Dims down to 2%
		SureSlide	6674	Best	1	6	Dims down to 11%
		Decora	6672	Best	1	6	Dims down to 10%
	Lutron	Skylark Countour	CTCL-153	Best	1	6	Dims down to 1%
		Diva	DVCL-153PL	Best	1	6	Dims down to 1%
		Maestro	MACL-153MLH	Best	1	6	Dims down to 8%
		Skylark	SCL-153P	Best	1	6	Dims down to 1%
		Toggler	TGCL-153PH	Best	1	6	Dims down to 1%
		Radio RA	RA2RR-6CL-PD	Best	1	6	Dims down to 7%
	Legrand	Harmony	DCL453-PTC	Best	1	6	Dims down to 6%
Harmony		HCL453PTC	Best	1	6	Dims down to 140%	
Adorne Paddle	ADPD453LM2	Good	1	6	Dims down to 26%		
Electronic Low Voltage	Leviton	Vizia	VP04	Good	1	6	Dims down to 14%
		IlumaTech	IP04	Best	1	6	Dims down to 10%
		Decora	6615-P	Bad	1	6	Dims down to 10%
	Lutron	Skylark Countour	CTELV-303P	Best	1	6	Dims down to 10%
		Diva	DVELV-300P	Best	1	6	Dims down to 10%
		Maestro	MAELV-600	Best	1	6	Dims down to 10%
		Skylark	SELVB-300P	Best	1	6	Dims down to 10%
		VIERTI	VTEL-600M-W	Good	1	6	Dims down to 12%
		Scene Director	SECELV	Good	1	6	Dims down to 25%
	Magentic Low Voltage	Leviton	Vizia	VPM-06	Good	3	6
Decora			6613-P	Best	1	6	Dims down to 12%
Lutron		Maestro	MALV-600	Good	1	6	Dims down to 10%, 2 minimum load without ghost
		Harmony	DVL703-PW	Best	1	6	Dims down to 12%
Titan	CDLV703-PW	Good	1	6	Dims down to 12%		
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMX1-BLZ	Good	1	6	Dims down to 15%
	Leviton	Decora Smart Wi-Fi	DXGHD-1BZ	N/A			
	Insteon	SwitchLin Remote Control dimmer		N/A			
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dims down to 10%
	Legrand	Adorne touch Wi-Fi TRU Universal	ADTH700RMTUW1	N/A			
	Legrand	Adorne Sof Tap Wi-Fi TRU Universal	ADTP700RMTUW1	N/A			
GE	Z WAVE	ZW300S	Best	1	6	Dims down to 3%	
Universal	Legrand	Adorne SoftTap	ADTP703TU	Good	1	6	Dims down to 18%
		Miro Decorator	DRD4-W	Best	1	6	Dims down to 4%
		Harmony	H703PTUTC	Good	1	6	Dims down to 20%
		Adorne Whisper	ADWR700MMTUW2	Best	1	6	Dims down to 1%
		Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims down to 1%
	Cooper	Decorator	DAL06P-C2-K-L	Best	1	6	Dims down to 2%
		Skye	SAL06P-W-K-L	Best	1	6	Dims down to 3%

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.
†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	ing observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
Low End (L.E.) Dead Travel	

Contact Information:
Bulbrite Industries Inc.
145 West Commercial Avenue
Moonachie, New Jersey 07074
PHONE: 1-800-528-5555
FAX: 1-800-441-7708
Email: ProductSupport@bulbrite.com
©2017 Bulbrite Industries Inc.
All Rights Reserved.