

DOT LED 1W, 12V AC/DC

REV08.23.16
ETL
Intertek






DOT-RD-1W-30D-30K-SA



DOT-SQ-1W-30D-30K-SA



DOT-RD-1W-90D-30K-SA



Description:

Recessed or surface-mount (using surface-mount collar provided), the Dot **LED** features solid aluminum construction and uses only 1 watt of warm white **LED** light. Ideal for cabinet illumination, the tiny but powerful round or square fixture provides a 30 degree beam spread. Round version is also available with a 90 degree beam spread. Includes 8 foot cord/plug port, wire clips and screws. Fixture plugs into 4- or 8-port hub, which distributes the low voltage power from **LED** power source. Fixtures use 12VAC power supplies and include 5 year warranty.

Finish:

Satin Aluminum or Bronze

Lamp Specification:

1 Watt, 64 total lumens (90 Degree), 61 total lumens (30 Degree), 12VAC or DC **LED**, 3000K, 80+CRI, 70% lumen maintenance based on 50,000 hours of operation

Dimming Information:

Dimmable with Lutron Diva or Skylark standard electronic low voltage dimmers. AC power supplies dim down to 20% before flickering and slight buzzing



Power Supply:

Hardwired: **TE-60L-12**

Plug-In: **TE-60L-12AC-P**

Weight:

.5 lb (0.23 kg)



D - Distance from DOT LED fixture
FC - Initial footcandles at the center of beam
DIA - Diameter

DOT	Type	Watts	Beam Spread	Color Temp (K)	Finish
DOT	RD	1W	30D	30K	SA
	RD Round SQ Square	1W 1 Watt	30D 30 degree 90D 90 degree (round only)	30K 3000 Kelvin	SA Satin Aluminum BZ Bronze

PROJECT:

FIXTURE
TYPE:

DATE:

EDGE
LIGHTING


POWER HUB FOR PUCKS & DOTS

REV08.23.16



8 Port Hub shown

6 foot cord connects
to LED power source



Description:

The 4 or 8 Port Hub distributes the 12V AC/DC low voltage power from LED transformer to a combination of 1 to 4 or 1 to 8 LED Puck or Dot lights. Includes 6 foot Power Feed Connector Cord and 3 clips.

Product	Type
HUB	4P
HUB Power Hub	4P 4 Port 8P 8 Port



12 Ft. Hub Extension Cord and Hub Connector

The 12 ft extension cord extends the Hub power cord or the Puck and Dot fixture cord. Includes 6 pieces of WC-1 wire clips. Use HUB-HUB-12 to link multiple Hubs together.

Product	Type	Length
HUB	EC	12
HUB Power Hub	EC HUB Extension Cord Hub to Hub	12 12 Feet



Wire Clips

Wire Clips keep wires organized. Secure with screws or double-sided tape (included). 3 wire clips provided for each fixture. Also sold separately.

Product	Type
WC	1
WC Wire Clip	1 Standard

PROJECT:

FIXTURE
TYPE:

DATE:

EDGE
LIGHTING

AC POWER FOR DOTS

REV08.23.16



Electronic 60 Watt AC Transformer with Rectangle Canopy Cover

TE-60L-12 Electronic 60 Watt 12 Volt AC hard wire fits inside single gang electrical box covered with a white 3" rectangular canopy, powering the Dots and Pucks.

Product	Wattage	Voltage	Type	Finish
TE	60L	12AC	3RE	WH
TE Transformer Electronic	60L 60 Watt LED	12AC 12 Volt AC	3RE 3 Inch Rectangle Canopy Cover	WH White



Electronic 60 Watt LED AC Transformer Plug-In

Plug-In version of the TE-60-12 Electronic 60 Watt 12 Volt AC Transformer includes 10 ft of cord and DC Connector to plug into the HUB-4P or HUB-8P powering the Dots and Pucks.

Product	Wattage	Voltage	Type
TE	60L	12AC	P
TE Transformer Electronic	60L 60 Watt LED	12AC 12 Volt AC	P Plug In



Electronic 60 Watt LED AC Transformer

TE-60L-12 Electronic 60 Watt 12 Volt AC Transformer converts standard 120 volt line voltage to 12 volts and features built-in short-circuit protection. Fits inside an electrical junction box. Minimum dimming load is 6 watts.

Product	Wattage	Voltage
TE	60L	12
TE Transformer Electronic	60L 60 Watt LED and Halogen	12 12 Volt AC



3" Rectangle and 4" Round Canopy Cover

The white rectangle or round canopy cover conceals the TE-60L-12 LED transformer (sold separately) inside a single gang box to power Dots and Pucks.

Product	Finish
3RE	WH
3RE 3 Inch Rectangle Canopy Cover	WH White
4RD	
4RD 4 Inch Round Canopy Cover	

PROJECT:

FIXTURE
TYPE:


DATE:



Application: Wiring Diagram for 4 Dot LED fixtures

Power Supply: 60 watt, 120 volt input, 12 volt AC output TE-60L-12

Dimming: Dimmable with low voltage electronic dimmer using power supply above.
See power supply spec sheet for additional details.
Lutron: Diva #DVELV-300P; Skylark #SELV-300P dimmers are recommended



PROJECT:

FIXTURE
TYPE:


DATE:

EDGE
LIGHTING

Application: Wiring diagram for 7 Dot LED fixtures

Power Supply: 60 watt, 120 volt input, 12 volt AC output TE-60L-12AC-P

Dimming: Dimmable with low voltage electronic dimmer using power supply above.
See power supply spec sheet for additional details.
Lutron: Diva #DVELV-300P; Skylark #SELV-300P dimmers are recommended



PROJECT:

FIXTURE
TYPE:

DATE:

PUCK LED 3W, 12V AC/DC

REV05.12.16
ETL
C-UL-1000-10



Surface Mount - Satin Aluminum



Surface Mount (Collar Included)




Recessed




Surface Mount - White




Surface Mount - Bronze



Recessed



Surface



Description:

Recessed or surface-mount, Puck **LED** features solid aluminum construction and uses only 3 watts of warm-white **LED** light. Ideal for under cabinet illumination. The tiny but very powerful round fixture is available with a 90 degree beam spread. Includes 8 foot cord/plug port, wire clips and screws. Fixture plugs into 4- or 8-port hub, which distributes the low voltage power from **LED** power source. Fixtures use 12VAC or 12VDC power supplies and include a 5 year warranty.

Finish:

Satin Aluminum, White or Bronze

Lamp Specification:

4 Total Watts, 138 total lumens, 12V AC or DC **LED**, 3070K, 84CRI, 70% lumen maintenance based on 50,000 hours of operation

Dimming Information:

Dimmable with Lutron Diva or Skylark standard electronic low voltage dimmers. AC power supplies dim down to 20% before flickering and slight buzzing

Power Supply:


Hardwired: **TE-60L-12**

Plug-In: **TE-60L-12AC-P**

Weight:

.5 lb (0.23 kg)

	Type	Watts	Beam Spread	Color Temp (K)	Finish
PUCK	RD	3W	90D	30K	SA
	RD Round	3W 3 Watts	90D 90 degree	30K 3070 Kelvin	SA Satin Aluminum WH White BZ Bronze



PROJECT:


FIXTURE
TYPE:

DATE:

EDGE
LIGHTING


POWER HUB FOR PUCKS & DOTS

REV05.12.16



Description:

The 4 or 8 Port Hub distributes the 12V AC/DC low voltage power from LED transformer to a combination of 1 to 4 or 1 to 8 LED Puck or Dot lights. Includes 6 foot Power Feed Connector Cord and 3 clips.



Product	Type
HUB	4P
HUB Power Hub	4P 4 Port 8P 8 Port



12 Ft. Hub Extension Cord and Hub Connector

The 12 ft extension cord extends the Hub power cord or the Puck and Dot fixture cord. Includes 6 pieces of WC-1 wire clips. Use HUB-HUB-12 to link multiple Hubs together.

Product	Type	Length
HUB	EC	12
HUB Power Hub	EC HUB Extension Cord Hub to Hub	12 12 Feet



Wire Clips

Wire Clips keep wires organized. Secure with screws or double-sided tape (included). 3 wire clips provided for each fixture. Also sold separately.

Product	Type
WC	1
WC Wire Clip	1 Standard

PROJECT:

FIXTURE
TYPE:

DATE:

EDGE
LIGHTING



Electronic 60 Watt AC Transformer with Rectangle Canopy Cover
TE-60L-12 Electronic 60 Watt 12 Volt AC hard wire fits inside single gang electrical box covered with a white 3" rectangular canopy, powering the Dots and Pucks.

Product	Wattage	Voltage	Type	Finish
TE	60L	12AC	3RE	WH
TE Transformer Electronic	60L 60 Watt LED	12AC 12 Volt AC	3RE 3 Inch Rectangle Canopy Cover	WH White



Electronic 60 Watt LED AC Transformer Plug-In
Plug-In version of the TE-60L-12 Electronic 60 Watt 12 Volt AC Transformer includes 10 ft of cord and DC Connector to plug into the HUB-4P or HUB-8P powering the Dots and Pucks.

Product	Wattage	Voltage	Type
TE	60L	12AC	P
TE Transformer Electronic	60L 60 Watt LED	12AC 12 Volt AC	P Plug In



Electronic 60 Watt LED AC Transformer
TE-60L-12 Electronic 60 Watt 12 Volt AC Transformer converts standard 120 volt line voltage to 12 volts and features built-in short-circuit protection. Fits inside an electrical junction box. Minimum dimming load is 6 watts.

Product	Wattage	Voltage
TE	60L	12
TE Transformer Electronic	60L 60 Watt LED and Halogen	12 12 Volt AC




3" Rectangle and 4" Round Canopy Cover
The white rectangle or round canopy cover conceals the TE-60L-12 LED transformer (sold separately) inside a single gang box to power Dots and Pucks.

Product	Finish
3RE	WH
3RE 3 Inch Rectangle Canopy Cover	WH White
4RD 4 Inch Round Canopy Cover	

Application: Electronic low-voltage dimming for 4 Puck LED fixtures

Power Supply: 60 watt, 120 volt input, 12 volt AC output **TE-60L-12**

Dimming: Dimmable with Lutron Diva #DVELV-300P or Skylark #SELV-300P standard electronic low voltage dimmers. AC power supplies dim down to 20% before flickering and slight buzzing



PROJECT:


FIXTURE
TYPE:

DATE:

Application: Electronic low-voltage dimming for 7 Puck LED fixtures

Power Supply: 60 watt, 120 volt input, 12 volt AC output **TE-60L-12AC-P**

Dimming: Dimmable with Lutron Diva #DVELV-300P or Skylark #SELV-300P standard electronic low voltage dimmers. AC power supplies dim down to 20% before flickering and slight buzzing
See power supply spec sheet for additional details.



PROJECT:

FIXTURE
TYPE:

DATE:

EDGE
LIGHTING