PRE-BENT MONORAIL


MONORAIL

DESIGNED BY GREGORY KAY REV 12.21.18



90° CURVE

Pre-Bent 90° Curve in 12" (30.5cm), 24" (61cm), 36" (91.4cm), 48" (122cm) or 60" (152.4cm) radius options offer versatility for numerous applications. Rated for maximum of 25 amps (300 watts at 12 volts, 600 watts at 24 volts). A pair of Conductive Connectors is included with each piece to connect other Monorail sections. Satin Nickel or Antique Bronze finish with Clear Insulator.



WEIGHT

• 12R: 0.49 lbs. (0.22 kg) • 24R: 0.98 lbs. (0.45 kg) • 36R: 1.47 lbs. (0.67 kg)

• 48R: 1.96 lbs. (0.89 kg) • 60R: 2.45 lbs. (1.12 kg)

STANDOFFS REQUIRED

· 12: 2 · 24: 2

· 36: 2

· 48: 3


• **60:** 3



60" (152.4cm) Radius

CIRCLE

Pre-Bent Circle features clean simple shapes for versatile applications. Rated for maximum of 25 amps (300 watts at 12 volts, 600 watts at 24 volts). Pair of Conductive and Isolating Connectors included. Satin Nickel or Antique Bronze finish with Clear Insulator.




WEIGHT

• 24C: 1.96 lbs. (0.89 kg) · 24: 3 • 36C: 2.95 lbs. (1.34 kg) · 36: 4 • 48C: 3.93 lbs. (1.78 kg) · 48: 5 • 60C: 4.91 lbs. (2.23 kg) · 60: 6 • 72C: 5.89 lbs. (2.67 kg) · 72: 7 • 84C: 6.87 lbs. (3.12 kg) · 84: 8 • 96C: 7.85 lbs. (3.56 kg) · 96: 9 • 108C: 8.84 lbs. (4.01 kg) • 120C: 9.82 lbs. (4.46 kg) · 120: 11


STANDOFFS REQUIRED

· 108: 10




S-CURVE

Pre-Bent S-Curve with 60° radius and 92" (234cm) linear length features a distinct design ideal for numerous applications. Rated for maximum of 25 amps (300 watts at 12 volts, 600 watts at 24 volts). Includes a pair of Conductive Connectors and two pairs of End Caps. Satin Nickel or Antique Bronze finish with Clear Insulator.



WEIGHT 2.5 lbs. (1.13 kg) STANDOFFS REQUIRED




FINISHES



LABELS Assembled in America





PROJECT FIXTURE TYPE DATE