

MULTIPLE RECESSED **AMIGO LED 15W**



TRIMLESS DOWNLIGHT

28715

HOUSING

- 18 gauge powder coated steel housing
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options) *

MESH PLATE

- Steel mesh plate (included)
- Perforated perimeter allows mud to bond to mounting surface leaving a seamless finish in the ceiling

LAMPING

- 1 x 15W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase.
- Beam angle: 40°
- Kelvin: 3000K
- Lumen per head: 1290lm
- CRI: 80+

ELECTRICAL

- Class 2 dimmable constant current driver (included)
- Driver box mates to fixture by 12" flexible BX cable
- Thermally protected
- Input voltage: 120V. For 277V and 347V input options consult Eurofase.

DIMENSIONS

- Cut hole: $\varnothing 3"$
- Fixture: $\varnothing 2 \frac{3}{4}" \times 5 \frac{3}{4}"$ H

PHOTOMETRICS

- See pg 124

CUSTOMIZATION



- For customization, please consult Eurofase

SPECIFICATION:



WATTS PER HEAD	LUMENS PER HEAD	KELVIN	DIMMABLE	CRI	BEAM ANGLE
15W	1290lm	3000K / 3500K	TRIAC	80+	40°

PRODUCT DIMENSION:



FINISHES:



-024 Black



-016 White



Mesh plate included



Driver box included

ORDERING GUIDE:

MODEL	KELVIN	FINISH
28715	-30 3000K	-024 Black
	-35 3500K	-016 White

EXAMPLE: 28715-30-024

*HOUSING OPTIONS (SOLD SEPARATELY):

Refer to page 151 for housing specification

30537-019

NEW CONSTRUCTION PLATE



Cut Hole $\varnothing 3"$
Dimension 11"L x 9"W x 1 3/8"H

30533-028
30533-011

AIR-TIGHT IC BOX
INSULATED CEILING BOX



Cut Hole $\varnothing 3"$
Dimension 11"L x 9"W x 9 1/2"H