

MULTIPLE RECESSED AMIGO LED 15W



TRIMLESS DOWNLIGHT

28717

HOUSING

- 18 gauge powder coated steel housing
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options)*

MESH PLATE

- Steel mesh plate (included)
- Perforated perimeter allows mud to bond to mounting surface leaving a seamless finish in the ceiling

LAMPING

- 1 x 15W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase.
- Beam angle: 40°
- Kelvin: 3000K
- Lumen per head: 1290lm
- CRI: 80+

ELECTRICAL

- Class 2 dimmable constant current driver (included)
- Driver box mates to fixture by 12" flexible BX cable
- Thermally protected
- Input voltage: 120V. For 277V and 347V input options consult Eurofase.

DIMENSIONS

- Cut hole: 3"L x 3"W
- Fixture: \varnothing 2 3/4" x 5 3/4"H

PHOTOMETRICS

- See pg 124

CUSTOMIZATION



- For customization, please consult Eurofase

SPECIFICATION:



WATTS PER HEAD	LUMENS PER HEAD	KELVIN	DIMMABLE	CRI	BEAM ANGLE
15W	1290lm	3000K / 3500K	TRIAC	80+	40°

PRODUCT DIMENSION:



3"L x 3"W

FINISHES:



-024 Black



-010 White



Mesh plate included



Driver box included

ORDERING GUIDE:

MODEL	KELVIN	FINISH
28717	-30 3000K	-024 Black
	-35 3500K	-010 White

EXAMPLE: 28717-30-024

*HOUSING OPTIONS (SOLD SEPARATELY):

Refer to page 151 for housing specification

30536-012

NEW CONSTRUCTION PLATE



Cut Hole 3"L x 3"W
Dimension 11"L x 9"W x 1 3/8"H

30532-023

30532-014

AIR-TIGHT IC BOX

INSULATED CEILING BOX



Cut Hole 3"L x 3"W
Dimension 11"L x 9"W x 9 1/2"H