



**TRIMLESS  
GIMBAL**

**28718**

**HOUSING**

- 18 gauge powder coated steel housing
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options) \*

**GIMBAL**

- Adjustable direction suit different application requirement
- Tilt: 30°

**MESH PLATE**

- Steel mesh plate (included)
- Perforated perimeter allows mud to bond to mounting surface leaving a seamless finish in the ceiling

**LAMPING**

- 1 x 15W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase.
- Beam angle: 40°
- Kelvin: 3000K
- Lumen per head: 1290lm
- CRI: 80+

**ELECTRICAL**

- Class 2 dimmable constant current driver (included)
- Driver box mates to fixture by 12" flexible BX cable
- Thermally protected
- Input voltage: 120V. For 277V and 347V input options consult Eurofase.

**DIMENSIONS**

- Cut hole: 3"L x 3"W
- Fixture: ø2 3/4" x 5 3/4"H

**PHOTOMETRICS**

- See pg 124

**CUSTOMIZATION**



- For customization, please consult Eurofase

**SPECIFICATION:**



WATTS PER HEAD	LUMENS PER HEAD	KELVIN	DIMMABLE	CRI	BEAM ANGLE	TILT
15W	1290lm	3000K / 3500K	TRIAC	80+	40°	30°

**PRODUCT DIMENSION:**



3" L X 3" W

**FINISHES:**



-028 Black



-017 White



Mesh plate included



Driver box included

**ORDERING GUIDE:**

MODEL	KELVIN	FINISH
28718	-30 3000K	-028 Black
	-35 3500K	-017 White

**EXAMPLE:** 28718-30-017

**\*HOUSING OPTIONS (SOLD SEPARATELY):**

*Refer to page 151 for housing specification*

**30536-012**

NEW CONSTRUCTION PLATE

**30532-023  
30532-014**

AIR-TIGHT IC BOX  
INSULATED CEILING BOX



Cut Hole 3"L x 3"W  
Dimension 11"L x 9"W x 1 3/8"H



Cut Hole 3"L x 3"W  
Dimension 11"L x 9"W x 9 1/2"H



MULTIPLE RECESSED AMIGO LED 15W