

MULTIPLE RECESSED AMIGO LED 15W



DOWNLIGHT

28719

HOUSING

- 18 gauge powder coated steel housing
- Remodel housing complete with adjustable mounting clips suitable for 1/2" and 5/8" drywall
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options) *

LAMPING

- 1 x 15W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase.
- Beam angle: 40°
- Kelvin: 3000K
- Lumen per head: 1290lm
- CRI: 80+

ELECTRICAL

- Class 2 dimmable constant current driver (included)
- Driver box mates to fixture by 12" flexible BX cable
- Thermally protected
- Input voltage: 120V. For 277V and 347V input options consult Eurofase.

DIMENSIONS

- Cut hole: $\varnothing 3 \frac{1}{4}$ "
- Fixture: $\varnothing 3 \frac{7}{8}$ " x $5 \frac{3}{4}$ "H

PHOTOMETRICS

- See pg 124

CUSTOMIZATION



- For customization, please consult Eurofase

SPECIFICATION:



WATTS PER HEAD	LUMENS PER HEAD	KELVIN	DIMMABLE	CRI	BEAM ANGLE
15W	1290lm	3000K / 3500K	TRIAC	80+	40°

PRODUCT DIMENSION:



$\varnothing 3 \frac{1}{4}$ "

FINISHES:



-028 Black



-014 White

ORDERING GUIDE:

MODEL	KELVIN	FINISH
28719	-30 3000K	-028 Black
	-35 3500K	-014 White

EXAMPLE: 28719-30-028



*HOUSING OPTIONS (SOLD SEPARATELY):

Refer to page 150 for housing specification

30534-018

NEW CONSTRUCTION PLATE

30530-026

AIR-TIGHT IC BOX

30530-010

INSULATED CEILING BOX



Cut Hole $\varnothing 3 \frac{1}{4}$ "
Dimension 11"L x 9"W x 1 3/8"H



Cut Hole $\varnothing 3 \frac{1}{4}$ "
Dimension 11"L x 9"W x 9 1/2"H