



## GIMBAL

### 28720

#### HOUSING

- 18 gauge powder coated steel housing
- Remodel housing complete with adjustable mounting clips suitable for 1/2" and 5/8" drywall
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options) \*

#### GIMBAL

- Adjustable direction suit different application requirement
- Tilt: 30°

#### LAMPING

- 1 x 15W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase.
- Beam angle: 40°
- Kelvin: 3000K
- Lumen per head: 1290lm
- CRI: 80+

#### ELECTRICAL

- Class 2 dimmable constant current driver (included)
- Driver box mates to fixture by 12" flexible BX cable
- Thermally protected
- Input voltage: 120V. For 277V and 347V input options consult Eurofase.

#### DIMENSIONS

- Cut hole:  $\varnothing 3 \frac{1}{4}"$
- Fixture:  $\varnothing 3 \frac{7}{8}" \times 5 \frac{3}{4}"$ H

#### PHOTOMETRICS

- See pg 124

#### CUSTOMIZATION



- For customization, please consult Eurofase

#### SPECIFICATION:



WATTS PER HEAD	LUMENS PER HEAD	KELVIN	DIMMABLE	CRI	BEAM ANGLE	TILT
15W	1290lm	3000K / 3500K	TRIAC	80+	40°	30°

#### PRODUCT DIMENSION:



#### FINISHES:



-021 Black



-010 White

#### ORDERING GUIDE:

MODEL	KELVIN	FINISH
28720	-30 3000K	-021 Black
	-35 3500K	-010 White

EXAMPLE: 28720-30-021



Driver box included

#### \*HOUSING OPTIONS (SOLD SEPARATELY):

Refer to page 150 for housing specification

30534-018

NEW CONSTRUCTION PLATE



Cut Hole  $\varnothing 3 \frac{1}{4}"$   
Dimension 11"L x 9"W x 1 3/8"H

30530-026  
30530-010

AIR-TIGHT IC BOX  
INSULATED CEILING BOX



Cut Hole  $\varnothing 3 \frac{1}{4}"$   
Dimension 11"L x 9"W x 9 1/2"H

