

# MULTIPLE RECESSED AMIGO LED 15W



## DOWNLIGHT

### 28721

#### HOUSING

- 18 gauge powder coated steel housing
- Remodel housing complete with adjustable mounting clips suitable for 1/2" and 5/8" drywall
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options) \*

#### LAMPING

- 1 x 15W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase.
- Beam angle: 40°
- Kelvin: 3000K/3500K
- Lumen per head: 1290lm
- CRI: 80+

#### ELECTRICAL

- Class 2 dimmable constant current driver (included)
- Driver box mates to fixture by 12" flexible BX cable
- Thermally protected
- Input voltage: 120V. For 277V and 347V input options consult Eurofase.

#### DIMENSIONS

- Cut hole: 3 1/4"L x 3 1/4"W
- Fixture: 3 7/8"L x 3 7/8"W x 5 3/4"H

#### PHOTOMETRICS

- See pg 124

#### CUSTOMIZATION



- For customization, please consult Eurofase

#### SPECIFICATION:



WATTS	LUMENS	KELVIN	DIMMABLE	CRI	BEAM ANGLE
15W	1290lm	3000K / 3500K	TRIAC	80+	40°

#### PRODUCT DIMENSION:




3 1/4" L X 3 1/4" W

#### FINISHES:



-025 Black



-017 White

#### ORDERING GUIDE:

MODEL	KELVIN	FINISH
28721	-30 3000K	-025 Black
	-35 3500K	-017 White

EXAMPLE: 28721-30-025



#### \*HOUSING OPTIONS (SOLD SEPARATELY):

Refer to page 150 for housing specification

30535-015

NEW CONSTRUCTION PLATE



Cut Hole 3 1/4"L x 3 1/4"W  
Dimension 11"L x 9"W x 1 3/8"H

30531-021  
30531-017

AIR-TIGHT IC BOX  
INSULATED CEILING BOX



Cut Hole 3 1/4"L x 3 1/4"W  
Dimension 11"L x 9"W x 9 1/2"H