

30304

HOUSING

- 18 gauge powder coated steel housing
- Remodel housing complete with adjustable mounting clips suitable for 1/2" and 5/8" drywall
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options) *

TRIM

- Extruded 6063 aluminum trim
- Powder coated finish
- Available in black, white and platinum

LAMPING

- 2 x 14.4W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase
- Beam angle: 120°
- Kelvin: 3000K
- Total lumens: 2360lm
- CRI: 80+

ELECTRICAL

- Junction box has two 1/2" and four 3/4" knockouts for through branch circuit wiring
- Thermally protected
- Input voltage: 120V. For 277V and 347V input options consult Eurofase

DIMENSIONS

- Cut hole: 9 1/2"L x 5 1/8"W
- Fixture: 10 1/2"L x 6 1/8"W x 6 1/2"H

PHOTOMETRICS

- See pg 100

CUSTOMIZATION



- For customization, please consult Eurofase

SPECIFICATION:




WATTS	LUMENS	KELVIN	DIMMABLE	CRI	BEAM ANGLE
28.8W	2360lm	3000K	TRIAC	80+	120°

PRODUCT DIMENSION:



9 1/2"L x 5 1/8"W

FINISHES:



-01 Black



-02 White



-0N Platinum

ORDERING GUIDE:

MODEL	FINISH
30304	-01 Black
	-02 White
	-0N Platinum

EXAMPLE: 30304-01

*HOUSING OPTIONS (SOLD SEPARATELY):

Refer to page 149 for housing specification

24052-016


NEW CONSTRUCTION PLATE



Cut Hole 9 1/2"L x 5 1/8"W
Dimension 17"L x 12 3/4"W x 1 3/8"H

30367-012
24072-014

AIRTIGHT IC BOX
INSULATED CEILING BOX



Cut Hole 9 1/2"L x 5 1/8"W
Dimension 17"L x 12 3/4"W x 11 1/2"H

