

Project:	
Fixture Type:	
Location:	
Contact/Phone:	

6" UNIVERSAL IC HOUSING

INCANDESCENT LAMPS

IC2 SERIES

PRODUCT DESCRIPTION

IC Air-Loc® double wall housing allows higher wattage and better lamp image cut-off • Energy efficient, sealed inner housing • Can be completely covered with insulation • When used with Air-Loc Gasket accessory or pre-installed gasket on mounting frame, stops infiltration and exfiltration of air, reducing heating and air cooling costs • Trims shown with Air-Loc symbol Air-Loc do not require a gasket.

PRODUCT SPECIFICATIONS

Lamp Lamp ratings based on trim selected - see pages 3-4.

Socket Medium base porcelain with nickel-plated copper screw shell
• Drop socket with spring to accommodate certain trim installation.

Trims Trim selection shown on pages 3-4.

Labels UL listed for through-branch wiring, damp locations and IP
• Product thermally protected against improper use of lamps • Union made • UL Listed/CSA certified • Trims 20, 21, 22, 239, 240, 241, 242, 243 and 9900 are wet location approved for covered ceiling applications • Trims 28, 29 are wet location approved for covered ceiling applications, when used with outdoor rated lamps.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.

Specifications subject to change without notice.

INSTALLATION


Real Nail® 3 Bar Hangers Telescoping, Patented (US Patent D552,969) Real Nail 3 system permits quick placement of housing anywhere within 24" O.C. joists or suspended ceilings • Integral T-bar notch and clip secures housing in suspended ceiling grid – no accessory clips required • 24" expansion stop allows quick placement of fixture in standard grid spacing • Bars scored in two locations for fast, clean breaking, allowing housing installation in tight applications • Bars captive to mounting frame • Edge-mounted for extra strength • Captive bugle-headed ring shank nail for quick one-step installation and easy removal with claw hammer for fixture relocation • Quick-Loc slot and oversized locking set screw lock fixture in position • Bar hanger foot contoured to align to bottom of construction joist • Alternate mounting holes included


Junction Box Pre-wired junction box provided with (6) ½" and (1) ¾" knockouts, (4) Non-metallic sheathed cable connectors and ground wire, U.L. listed/CSA certified for through-branch wiring, maximum 8 No. 12 AWG 90° C branch circuit conductors (3 in, 3 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots • **Woptions** are supplied with **push-in electrical connectors** for fast installation.

Mounting Frame 22-gauge die-formed galvanized steel mounting frame • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation • Pre-installed Air-Loc gasket for **G options**.

Housing IC housing, .032" aluminum sealed for Air-Loc Compliance • Access door for junction box accessibility • Inner housing is vertically adjustable to accommodate up to a 1" ceiling thickness.

DIMENSIONS





67/8" CEILING CUTOUT

ACCESSORIES

Catalog No.	Description	
ALG6	Air-Loc Gasket	

To order, specify catalog number.

PRODUCT CODES

Catalog N	lumber	Input Voltage	Lamp Rating
IC2	6" Incandescent New Construction Deluxe IC Housing	120V	A19/A21/BR30/BR40/MR16/PAR16/PAR20/PAR30/PAR30L/PAR38/R20/R30 (See pages 3-4 for max. trim rating)
IC2 G	6" Incandescent New Construction Deluxe IC Housing with pre-installed Air-Loc gasket	120V	A19/A21/BR30/BR40/MR16/PAR16/PAR20/PAR30/PAR30L/PAR38/R20/R30 (See pages 3-4 for max. trim rating)
IC2 W	6" Incondescent New Construction Deluxe IC Housing with push-in electrical connectors for fast, secure installation	120V	A19/A21/BR30/BR40/MR16/PAR16/PAR20/PAR30/PAR30L/PAR38/R20/R30 (See pages 3-4 for max. trim rating)
IC2 W G	6" Incandescent New Construction Deluxe IC Housing with push-in electrical connectors and pre-installed Air-Loc gasket	120V	A19/A21/BR30/BR40/MR16/PAR16/PAR20/PAR30/PAR30L/PAR38/R20/R30 (See pages 3-4 for max. trim rating)

Housing and trim can be ordered together or separate, but will always ship separately.

6" UNIVERSAL IC HOUSING

INCANDESCENT LAMPS

IC2 SERIES

TRIMS/LAMPS

		Catalog Number	Description	Max. Lamp Rating				
		23 BWH	6" Downlight Pinhole with Baffle Trim - Black Baffle, White Trim Ring	50W PAR20/R20				
**		24 BWH 24 BSC 24 BABZ 24 BBL 24 WWH	6" Downlight Tapered Baffle Trim - Black Baffle, White Trim Ring 6" Downlight Tapered Baffle Trim - Black Baffle, Satin Chrome Trim Ring 6" Downlight Tapered Baffle Trim - Black Baffle, Classic Aged Bronze Trim Ring 6" Downlight Tapered Baffle Trim - Black Baffle, Black Trim Ring 6" Downlight Tapered Baffle Trim - White Baffle, White Trim Ring	75W PAR3OL, 65W BR3O				
**		25 BWH 25 BSC 25 BABZ 25 BBL 25 WWH	6" Downlight Straight Baffle Trim - Black Baffle, White Trim Ring 6" Downlight Straight Baffle Trim - Black Baffle, Safin Chrome Trim Ring 6" Downlight Straight Baffle Trim - Black Baffle, Classic Aged Bronze Trim Ring 6" Downlight Straight Baffle Trim - Black Baffle, Black Trim Ring 6" Downlight Straight Baffle Trim - White Baffle, White Trim Ring	85W BR40, 90W PAR38				
**		26 CWH 26 GWH 26 BWH 26 PTSC 26 WWH 26 HZWH 26 WHZWH	6" Downlight Straight Cone Trim - Clear Alzak®, White Trim Ring 6" Downlight Straight Cone Trim - Gold, White Trim Ring 6" Downlight Straight Cone Trim - Black, White Trim Ring 6" Downlight Straight Cone Trim - Pewter, Satin Chrome Trim Ring 6" Downlight Straight Cone Trim - White, White Trim Ring 6" Downlight Straight Cone Trim - Haze, White Trim Ring 6" Downlight Straight Cone Trim - Wheat Haze, White Trim Ring 6" Downlight Straight Cone Trim - Wheat Haze, White Trim Ring	90W PAR38, 85W BR40				
**		27 CWH 27 GWH 27 BWH 27 PTSC 27 WWH 27 HZWH 27 WHZWH 27 WHZMBZ	6" Downlight Tapered Cone Trim - Clear Alzak® Cone, White Trim Ring 6" Downlight Tapered Cone Trim - Gold Cone, White Trim Ring 6" Downlight Tapered Cone Trim - Black Cone, White Trim Ring 6" Downlight Tapered Cone Trim - Pewter Cone, Sotin Chrome Trim Ring 6" Downlight Tapered Cone Trim - White Cone, White Trim Ring 6" Downlight Tapered Cone Trim - Wheat Haze Cone, White Trim Ring 6" Downlight Tapered Cone Trim - Wheat Haze Cone, White Trim Ring 6" Downlight Tapered Cone Trim - Wheat Haze Cone, Classic Aged Bronze Trim Ring	75W PAR3OL, 65W BR3O				
	AIR-LOC	28 BWH ◆◆ 28 WWH ◆◆	6" Downlight Ultra Trim Baffle Fully Enclosed Trim - Block Baffle, White Trim Ring 6" Downlight Ultra Trim Baffle Fully Enclosed Trim - White Baffle, White Trim Ring	75W A19, 100W PAR38, 75W PAR30/30L, 85W BR30, 120W BR40				
	AIR-Loc	29 CWH ◆◆ 29 WWH ◆◆	6" Downlight Ultra Trim Cone Fully Enclosed Trim - Clear Cone, White Trim Ring 6" Downlight Ultra Trim Cone Fully Enclosed Trim - White Cone, White Trim Ring	100W A19, 100W PAR38, 75W PAR30/30L, 85W BR30, 120W BR40				
		230 CBWH 230 CWWH	$6'' \ Downlight \ Economy \ A-Lamp \ Reflector \ with \ Baffle \ Trim - Clear \ with \ Black, \ Black \ Trim \ Ring$ $6'' \ Downlight \ Economy \ A-Lamp \ Reflector \ with \ Baffle \ Trim - Clear \ with \ White, \ White \ Trim \ Ring$	100W A19				
		232 CWH 232 GWH 232 WWH 232 HZWH 232 WHZWH	6" Downlight A-Lamp Reflector Trim - Clear Alzak®, White Trim Ring 6" Downlight A-Lamp Reflector Trim - Gold Alzak®, White Trim Ring 6" Downlight A-Lamp Reflector Trim - White, White Trim Ring 6" Downlight A-Lamp Reflector Trim - Haze, White Trim Ring 6" Downlight A-Lamp Reflector Trim - Wheat Haze, White Trim Ring	100W A19, 150W A21 100W A19, 150W A21 75W A19 100W A19, 150W A21 100W A19, 150W A21				
		233 CWH	6" Downlight A-Lamp Reflector with Black Baffle Trim - Clear Alzak®, White Trim Ring	75W A19		75%" O.D. (except Cat. Nos. 228, 9024 - 8" O.D., Cat. No. 9702 - 73/4" O.D.).		
**		244S BWH 244S WWH	6" Downlight Shallow Baffle Trim - Black Baffle, White Trim Ring 6" Downlight Shallow Baffle Trim - White Baffle, White Trim Ring	75W PAR30/30L, 65W BR30		ners specifically designed for low voltage ansformers.		
**	AIR-LOC AIR-LOC	247S CWH 247S GWH 247S BWH 247S HZWH	6" Downlight Shallow Cone Trim - Clear Alzak® Cone, White Trim Ring 6" Downlight Shallow Cone Trim - Gold Alzak® Cone, White Trim Ring 6" Downlight Shallow Cone Trim - Black Alzak® Cone, White Trim Ring 6" Downlight Shallow Cone Trim - Haze Cone, White Trim Ring	75W PAR30/30L, 65W BR30		egistered trademark of Alcoa Corp. anada when insulation is present, Type IC at be used. JUNO IC housings meet IECC Energy Code		
		250 WH 6" Downlight Open Frame Trim - White 250 SC 6" Downlight Open Frame Trim - Safin Chrome		65W BR30	AIR-LOC	Air-Loc® rated trims are pre-gasketed for minimum air leakage with IC housings.		
		251 WH		100W BR40	◆ UL Listed for use in wet location.			
			6" Downlight Open Frame Trim - White			d for use in wet location with outdoor rated lamp.		
**		254 BWH 254 WWH	6" Downlight Deep Baffle Trim - Black Baffle, White Trim Ring 6" Downlight Deep Baffle Trim - White Baffle, White Trim Ring	75W PAR30, 100W PAR38		TR6 Trim Ring compatible with 24, 25, 26, 247S, 254, 257, 264, 267, 9900 trims.		

6" UNIVERSAL IC HOUSING

INCANDESCENT LAMPS

IC2 SERIES

TRIMS/LAMPS (cont.)

LOW VOLTAGE TRIMS WITH TRANSFORMER*

	 Catalog Number	Description	Max. Lamp Rating		Catalog Number	Description	Max. Lamp Rating
**	257 CWH 257 BWH 257 GWH 257 HZWH 257 WHZWH	6" Downlight Deep Cone Trim - Clear Alzok® Cone, White Trim Ring 6" Downlight Deep Cone Trim - Black Alzak® Cone, White Trim Ring 6" Downlight Deep Cone Trim - Gold Alzak® Cone, White Trim Ring 6" Downlight Deep Cone Trim - Haze Cone, White Trim Ring 6" Downlight Deep Cone Trim - Wheat Haze Cone, White Trim Ring	75W PAR30, 100W PAR38		424 BWH 427 WWH	6" Adjustable Pinhole with Baffle Trim - Black Baffle, White Trim Ring 6" Adjustable Cylinder Spotlight in Baffle Trim	35W MR16 50W MR16
	224 BWH 224 WWH	6" Adjustable Gimbal Ring in Baffle Trim - Black Baffle, White Trim Ring 6" Adjustable Gimbal Ring in Baffle Trim - White Baffle, White Trim Ring Can also be used w/med. screw base lamps	75W PAR38/3 Side Prong			- White Baffle, White Trim Ring	
	226 BWH 226 WWH	$6^{\prime\prime}$ Adjustable Cylinder Spotlight in Baffle Trim - Black Baffle, White Trim Ring $6^{\prime\prime}$ Adjustable Cylinder Spotlight in Baffle Trim - White Baffle, White Trim Ring	60W PAR16				
	228 WH	6" Adjustable Regressed Eyeball Trim - White	50W PAR20/R20				
	229 WH 229 SC 229 ABZ 229 BL	6" Adjustable Regressed Eyeball Trim - White 6" Adjustable Regressed Eyeball Trim - Satin Chrome 6" Adjustable Regressed Eyeball Trim - Classic Aged Bronze 6" Adjustable Regressed Eyeball Trim - Block	75W PAR3OL, 65W BR3O				
	248 WWH	6" Adjustable Regressed Eyeball in Baffle Trim - White Baffle, White Trim Ring	50W PAR20/R20				
	249 BWH 249 WWH	6" Adjustable Regressed Eyeball in Baffle Trim - Black Baffle, White Trim Ring 6" Adjustable Regressed Eyeball in Baffle Trim - White Baffle, White Trim Ring	75W PAR30L, 65W BR30				
* *	264 BWH 264 WWH	6" Adjustable Tapered Baffle Trim - Black Baffle, White Trim Ring 6" Adjustable Tapered Baffle Trim - White Baffle, White Trim Ring	75W PAR30				
**	267 CWH 267 GWH 267 BWH 267 HZWH 267 WHZWH	6" Adjustable Tapered Cone Trim - Clear Alzak® Cone, White Trim Ring 6" Adjustable Tapered Cone Trim - Gold Alzak® Cone, White Trim Ring 6" Adjustable Tapered Cone Trim - Black Alzak® Cone, White Trim Ring 6" Adjustable Tapered Cone Trim - Haze Cone, White Trim Ring 6" Adjustable Tapered Cone Trim - Wheat Haze Cone, White Trim Ring	75W PAR30				
AIR-LOC	20 WH ◆ 20 PW ◆	6" Lensed Albalite Trim - White 6" Lensed Albalite Trim - Plastic White	40W A19				
	240 WH ◆ 240 PW ◆	6" Lensed Albolite with Reflector Trim - White 6" Lensed Albolite with Reflector Trim - Plastic White	60W A19				
AIR-LOC	21 WH ◆ 21 PW ◆	6" Lensed Drop Opal Trim - White 6" Lensed Drop Opal Trim - Plastic White	40W A19				
	241 WH ◆ 241 PW ◆	6" Lensed Drop Opal with Reflector Trim - White 6" Lensed Drop Opal with Reflector Trim - Plastic White	60W A19				
AIR-LOC	242 WH ◆ 242 SC ◆ 242 ABZ ◆	6" Lensed Frosted Lens with Clear Center Trim - White 6" Lensed Frosted Lens with Clear Center Trim - Satin Chrome 6" Lensed Frosted Lens with Clear Center Trim - Classic Aged Bronze	75W PAR38, 60W PAR38IR				
	22 WH ◆	6" Lensed Fresnel Trim - White	40W A19	T : C:	75/" 0 0 1	cept Cat. Nos. 228,	
AIR-LOC	239 WH ◆	6" Lensed Frosted Lens Trim - White	40W A19	229, 2	241, 9024 - 8" O.D	D., Cat. No. 9702 - 73/2	" O.D.).
	261 BWH 261 WWH	6" Wall Wash Scoop Trim - 6" Wall Wash Scoop Trim -	40W A19	magne	tic transformers.	y designed for low volta	ige
AIR-LOC	243 WH ◆	6" Decorative Swirled Etched Opal Glass Trim - White	60W A19	Note: I		emark of Alcoa Corp. sulation is present, Type	e IC
	9324 SC	6" Decorative Luminous Disc Frosted Trim - Satin Chrome	65W BR30		requirements	usings meet IECC Ener per ASTM E283.	rgy Code
	9702	6" Decorative Luminous Collar Frosted Trim - Luminous Collar (Frosted)	75W BR30	Air-Lo	Air-Loc® rated	d trims are pre-gaskete leakage with IC housi	
	9024 WWH	6" Decorative Octagonal Trim - White, White Trim Ring	65W BR30	◆ UL Li	sted for use in wet l	ocation.	
	9524 SC	6" Decorative Metal Band Trim - Satin Chrome	65W BR30			et location with outdoor	•
AIR-LOC * *	9900 WH ◆	6" Decorative Fluted Drop Opal Trim - White	60W A19	** Ni 27, 24	OTE: TR6 Trim Ring 14S, 247S, 254, 25	compatible with 24, 2 57, 264, 267, 9900 tri	5, 26, ims.